

Grain Floating

Collection	Grain + Pigment	
Style Number	0364V	
Construction	Heavy Comm Luxury Vinyl Tile W/ In*step Backing	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating	

Packaging

Pieces Per Carton	10 pcs	
Area Per Carton	24.13 sq ft	2.24 sq m
Weight Per Carton	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Radiant Panel (Astm E648)	Passes, Class I
Coefficient Of Friction (Astm D2407, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
7.31 Kg CO₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | 3rd Party Certified
Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

[Installation Guidelines](#)
[Maintenance](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways


					
Cocoa 64103 LRV 21 L* 52.91 V3 - Moderate Variation	Glow 64105 LRV 37.1 L* 67.33	Parchment 64111 LRV 43.4 L* 71.79 V2 - Slight Variation	Alabaster 64114 LRV 42.4 L* 71.17 V3 - Moderate Variation	Buff 64140 LRV 28.3 L* 60.17 V2 - Slight Variation	Nutshell 64150 LRV 12.6 L* 42.09 V2 - Slight Variation

 <div>Ashen 64155 LRV 27 L* 59 V2 - Slight Variation</div>	 <div>Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation</div>	 <div>Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation</div>	 <div>Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation</div>	 <div>Alloy 64515 LRV 37.4 L* 67.56</div>	 <div>Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation</div>
 <div>Mercury 64530 LRV 25.5</div>	 <div>Char 64549 LRV 7.1 V2 - Slight Variation</div>	 <div>Cinder 64557 LRV 16.6 L* 47.78</div>	 <div>Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation</div>	 <div>Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation</div>	 <div>Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation</div>
 <div>Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation</div>	 <div>Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation</div>	 <div>Antler 64761 LRV 18.4 V2 - Slight Variation</div>	 <div>Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation</div>		

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1




Uniform Appearance

V2




Slight Variation

V3



Moderate Variation

V4



Substantial Variation