

Grain Floating

Collection	Grain + Pigment	
Style Number	0364V	
Construction	Heavy Comm Luxury Vinyl Tile W/ In*step Backing	
class	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating	

Packaging

Pieces Per Box	10 pcs	
Area Per Box	24.13 sq ft	2.24 sq m
Weight Per Box	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

performance + testing

residual indentation (ASTM F1914)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   3rd Party Certified
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	<b>FloorScore® Certified</b>

[Installation Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



Cocoa 64103  
LRV 21 | L\* 52.91  
V3 - Moderate Variation



Glow 64105  
LRV 37.1 | L\* 67.33



Parchment 64111  
LRV 43.4 | L\* 71.79  
V2 - Slight Variation



Alabaster 64114  
LRV 42.4 | L\* 71.17  
V3 - Moderate Variation



Buff 64140  
LRV 28.3 | L\* 60.17  
V2 - Slight Variation



Nutshell 64150  
LRV 12.6 | L\* 42.09  
V2 - Slight Variation



Ashen 64155  
LRV 27 | L\* 59  
V2 - Slight Variation



Bare 64200  
LRV 39.1 | L\* 68.82  
V2 - Slight Variation



Honey 64240  
LRV 26 | L\* 58.01  
V2 - Slight Variation



Fog 64327  
LRV 17.8 | L\* 49.19  
V3 - Moderate Variation



Alloy 64515  
LRV 37.4 | L\* 67.56



Weathered 64518  
LRV 29.5 | L\* 61.24  
V2 - Slight Variation



Mercury 64530  
LRV 25.5



Char 64549  
LRV 7.1  
V2 - Slight Variation



Cinder 64557  
LRV 16.6 | L\* 47.78



Earthen 64710  
LRV 10 | L\* 37.92  
V3 - Moderate Variation



Bark 64720  
LRV 12.5 | L\* 41.94  
V2 - Slight Variation



Clove 64740  
LRV 7.7 | L\* 33.32  
V2 - Slight Variation



Chickory 64752  
LRV 6.9 | L\* 31.68  
V2 - Slight Variation



Russet 64760  
LRV 7.4 | L\* 32.69  
V2 - Slight Variation



Antler 64761  
LRV 18.4  
V2 - Slight Variation



Ginger 64820  
LRV 15.2 | L\* 45.94  
V2 - Slight Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

