

Grain Floating

Collection	Grain + Pigment	
Style Number	0364V	
Construction	Heavy Comm Luxury Vinyl Tile W/In*step Backing	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.S.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating	

Packaging

Pieces per Carton	10 pcs	
Area per Carton	24.13 sq ft	2.24 sq m
Weight per Carton	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1100 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes	
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.		

Warranties

15 Year Commercial Limited Warranty

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.59 Kg CO ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	GSA Approved
	CE Marking (EN 14041) 3rd Party Certified
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

[Installation Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Cocoa 64103
LRV 21 | L* 52.91
V3 - Moderate Variation



Glow 64105
LRV 37.1 | L* 67.33



Parchment 64111
LRV 43.4 | L* 71.79
V2 - Slight Variation



Alabaster 64114
LRV 42.4 | L* 71.17
V3 - Moderate Variation



Buff 64140
LRV 28.3 | L* 60.17
V2 - Slight Variation



Nutshell 64150
LRV 12.6 | L* 42.09
V2 - Slight Variation




Ashen 64155
LRV 27 | L* 59
V2 - Slight Variation



Bare 64200
LRV 39.1 | L* 68.82
V2 - Slight Variation



Honey 64240
LRV 26 | L* 58.01
V2 - Slight Variation



Fog 64327
LRV 17.8 | L* 49.19
V3 - Moderate Variation



Alloy 64515
LRV 37.4 | L* 67.56



Weathered 64518
LRV 29.5 | L* 61.24
V2 - Slight Variation



Mercury 64530
LRV 25.5



Char 64549
LRV 7.1
V2 - Slight Variation



Cinder 64557
LRV 16.6 | L* 47.78



Earthen 64710
LRV 10 | L* 37.92
V3 - Moderate Variation



Bark 64720
LRV 12.5 | L* 41.94
V2 - Slight Variation



Clove 64740
LRV 7.7 | L* 33.32
V2 - Slight Variation



Chickory 64752
LRV 6.9 | L* 31.68
V2 - Slight Variation



Russet 64760
LRV 7.4 | L* 32.69
V2 - Slight Variation




Antler 64761
LRV 18.4
V2 - Slight Variation




Ginger 64820
LRV 15.2 | L* 45.94
V2 - Slight Variation

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1


Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation

