

Grain Floating

Collection	Grain + Pigment	
Style Number	0364V	
Construction	Heavy Comm Luxury Vinyl Tile W/In*step Backing	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.S.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating	

Packaging

Pieces per Carton	10 pcs	
Area per Carton	24.13 sq ft	2.24 sq m
Weight per Carton	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1100 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.59 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	GSA Approved
	CE Marking (EN 14041) 3rd Party Certified
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cocoa 64103 LRV 21 L* 52.91 V3 - Moderate Variation	Glow 64105 LRV 37.1 L* 67.33	Parchment 64111 LRV 43.4 L* 71.79 V2 - Slight Variation	Alabaster 64114 LRV 42.4 L* 71.17 V3 - Moderate Variation	Buff 64140 LRV 28.3 L* 60.17 V2 - Slight Variation	Nutshell 64150 LRV 12.6 L* 42.09 V2 - Slight Variation
					
Ashen 64155 LRV 27 L* 59 V2 - Slight Variation	Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation	Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation	Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation	Alloy 64515 LRV 37.4 L* 67.56	Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation
					
Mercury 64530 LRV 25.5	Char 64549 LRV 7.1 V2 - Slight Variation	Cinder 64557 LRV 16.6 L* 47.78	Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation	Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation	Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation
					
Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation	Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation	Antler 64761 LRV 18.4 V2 - Slight Variation	Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

