

Grain Floating

Colección	Grain + Pigment	
Número De Estilo	0364V	
Construcción	Lvt Comercial De Tráfico Severo Con Sistema De Base In*step	
clase	Class III, Type B	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensiones Reales	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.157 in	4 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating	

Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	24.13 sq ft	2.24 sq m
Peso Por Caja	33.72 lbs	15.3 kg



Método De Instalación Recomendado



Stagger

Productos Que Combinan

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
11.59 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado Tercerizado
Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
- X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
- Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
- X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Contribución Para Créditos Leed

- Crédito MR: Divulgación y optimización de productos de construcción
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales
- Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)
- Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore® Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.



Visit shawcontract.com/testing for more information.

Available Colorways

					
Cocoa 64103 LRV 21 L* 52.91 V3 - Moderate Variation	Glow 64105 LRV 37.1 L* 67.33	Parchment 64111 LRV 43.4 L* 71.79 V2 - Slight Variation	Alabaster 64114 LRV 42.4 L* 71.17 V3 - Moderate Variation	Buff 64140 LRV 28.3 L* 60.17 V2 - Slight Variation	Nutshell 64150 LRV 12.6 L* 42.09 V2 - Slight Variation
					
Ashen 64155 LRV 27 L* 59 V2 - Slight Variation	Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation	Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation	Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation	Alloy 64515 LRV 37.4 L* 67.56	Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation
					
Mercury 64530 LRV 25.5	Char 64549 LRV 7.1 V2 - Slight Variation	Cinder 64557 LRV 16.6 L* 47.78	Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation	Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation	Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation
					
Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation	Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation	Antler 64761 LRV 18.4 V2 - Slight Variation	Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

