

Grain Floating

Colección	Grain + Pigment	
Número De Estilo	0364V	
Construcción	Lvt Comercial De Tráfico Severo Con Sistema De Base In*step	
clase	Class III, Type B	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensiones Reales	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.157 in	4 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating	
Embalaje		
Piezas Por Caja	10 pcs	
Área Por Caja	24.13 sq ft	2.24 sq m
Peso Por Caja	33.72 lbs	15.3 kg



Método De Instalación Recomendado



Stagger

Productos Que Combinan

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.59 Kg Co ₂ /M²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado Tercerizado
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales	Health Product Declaration (HPD) 100 Ppm Disclosure
Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Cocoa 64103 LRV 21 L* 52.91 V3 - Moderate Variation</div>	 <div>Glow 64105 LRV 37.1 L* 67.33</div>	 <div>Parchment 64111 LRV 43.4 L* 71.79 V2 - Slight Variation</div>	 <div>Alabaster 64114 LRV 42.4 L* 71.17 V3 - Moderate Variation</div>	 <div>Buff 64140 LRV 28.3 L* 60.17 V2 - Slight Variation</div>	 <div>Nutshell 64150 LRV 12.6 L* 42.09 V2 - Slight Variation</div>
 <div>Ashen 64155 LRV 27 L* 59 V2 - Slight Variation</div>	 <div>Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation</div>	 <div>Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation</div>	 <div>Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation</div>	 <div>Alloy 64515 LRV 37.4 L* 67.56</div>	 <div>Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation</div>
 <div>Mercury 64530 LRV 25.5</div>	 <div>Char 64549 LRV 7.1 V2 - Slight Variation</div>	 <div>Cinder 64557 LRV 16.6 L* 47.78</div>	 <div>Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation</div>	 <div>Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation</div>	 <div>Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation</div>
 <div>Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation</div>	 <div>Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation</div>	 <div>Antler 64761 LRV 18.4 V2 - Slight Variation</div>	 <div>Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation</div>		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



