

Grain Floating

Collection	Grain + Pigment	
Numéro De Style	0364V	
Construction	Carreau De Vinyle De Luxe Heavy Comm Avec Support In*step	
classe	Class III, Type B	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensions Réelles	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.157 in	4 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating	

Emballage

Pièces Par Carton	10 pcs	
Surface Par Carton	24.13 sq ft	2.24 sq m
Poids Par Carton	33.72 lbs	15.3 kg



Méthodes d'Installation Conseillées



Stagger

Coordination Des Produits

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

performance + Tests et essai

poinçonnement rémanent (ASTM F1914)	Passes
résistance à la chaleur (ASTM F1514)	Passes
résistance à la lumière (ASTM F1515)	Passes
résistance chimique (ASTM F925)	Passes
Essai au panneau radiant (Astm E648)	Passes, Class I
coefficient de frottement (ASTM D2407, résistance au glissement)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Agréé

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
11.59 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certifié Par Un Tiers
Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt
- X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt
- Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt
- X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants
Ortho-Phthalates
FloorScore Certificate

Contribution Au Certificat Vert Leed

- « Crédit MR : Divulcation et optimisation des produits de construction
- « Crédit MR : Divulcation et optimisation des produits de construction

Health Product Declaration (HPD) | 100 Ppm Disclosure
3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways



Cocoa 64103
LRV 21 | L* 52.91
V3 - Moderate Variation



Glow 64105
LRV 37.1 | L* 67.33




Parchment 64111
LRV 43.4 | L* 71.79
V2 - Slight Variation



Alabaster 64114
LRV 42.4 | L* 71.17
V3 - Moderate Variation



Buff 64140
LRV 28.3 | L* 60.17
V2 - Slight Variation



Nutshell 64150
LRV 12.6 | L* 42.09
V2 - Slight Variation




Ashen 64155
LRV 27 | L* 59
V2 - Slight Variation



Bare 64200
LRV 39.1 | L* 68.82
V2 - Slight Variation



Honey 64240
LRV 26 | L* 58.01
V2 - Slight Variation



Fog 64327
LRV 17.8 | L* 49.19
V3 - Moderate Variation



Alloy 64515
LRV 37.4 | L* 67.56



Weathered 64518
LRV 29.5 | L* 61.24
V2 - Slight Variation



Mercury 64530
LRV 25.5



Char 64549
LRV 7.1
V2 - Slight Variation



Cinder 64557
LRV 16.6 | L* 47.78



Earthen 64710
LRV 10 | L* 37.92
V3 - Moderate Variation



Bark 64720
LRV 12.5 | L* 41.94
V2 - Slight Variation



Clove 64740
LRV 7.7 | L* 33.32
V2 - Slight Variation



Chickory 64752
LRV 6.9 | L* 31.68
V2 - Slight Variation



Russet 64760
LRV 7.4 | L* 32.69
V2 - Slight Variation



Antler 64761
LRV 18.4
V2 - Slight Variation



Ginger 64820
LRV 15.2 | L* 45.94
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

