

Grain Floating

Coleção	Grain + Pigment	
Número Do Produto	0364V	
Construção	Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step	
classe	Class III, Type B	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 121 cm l
Dimensões Reais	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.157 in	4 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating	

Empacotamento

Peças Por Caixa	10 pcs	
Área Por Caixa	24.13 sq ft	2.24 sq m
Peso Por Caixa	33.72 lbs	15.3 kg



Método De Instalação Recomendado



Stagger

Produtos Coordenados

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

desempenho + teste

recuo residual (ASTM F1914)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
painel radiante (ASTM E648)	Passes, Class I
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)

Atributos + Certificações

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
11.59 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado 3rd Party
Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
- X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
- Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
- X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Crédito De Contribuição

- MR Credit: Divulgação e otimização de produtos de construção
- Ingredientes materiais - Opção 1: Relatório de ingredientes materiais
- MR Credit: Divulgação e otimização de produtos de construção
- Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)
- Crédito de EQ: Materiais de baixa emissão
- Opção 1: cálculos de categoria de produto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore® Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Cocoa 64103 LRV 21 L* 52.91 V3 - Moderate Variation</div>	 <div>Glow 64105 LRV 37.1 L* 67.33</div>	 <div>Parchment 64111 LRV 43.4 L* 71.79 V2 - Slight Variation</div>	 <div>Alabaster 64114 LRV 42.4 L* 71.17 V3 - Moderate Variation</div>	 <div>Buff 64140 LRV 28.3 L* 60.17 V2 - Slight Variation</div>	 <div>Nutshell 64150 LRV 12.6 L* 42.09 V2 - Slight Variation</div>
 <div>Ashen 64155 LRV 27 L* 59 V2 - Slight Variation</div>	 <div>Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation</div>	 <div>Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation</div>	 <div>Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation</div>	 <div>Alloy 64515 LRV 37.4 L* 67.56</div>	 <div>Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation</div>
 <div>Mercury 64530 LRV 25.5</div>	 <div>Char 64549 LRV 7.1 V2 - Slight Variation</div>	 <div>Cinder 64557 LRV 16.6 L* 47.78</div>	 <div>Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation</div>	 <div>Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation</div>	 <div>Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation</div>
 <div>Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation</div>	 <div>Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation</div>	 <div>Antler 64761 LRV 18.4 V2 - Slight Variation</div>	 <div>Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation</div>		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



