

Grain Floating

Coleção	Grain + Pigment	
Número Do Produto	0364V	
Construção	Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step	
classe	Class III, Type B	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 121 cm l
Dimensões Reais	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.157 in	4 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating	

Empacotamento

Peças Por Caixa	10 pcs	
Área Por Caixa	24.13 sq ft	2.24 sq m
Peso Por Caixa	33.72 lbs	15.3 kg



Método De Instalação Recomendado



Stagger

Produtos Coordenados

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
7.31 Kg CO₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado 3rd Party
Country of Origin | Imported

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais

Health Product Declaration (HPD) | 100 Ppm Disclosure

MR Credit: Divulgação e otimização de produtos de construção
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

FloorScore Certified

Installation Guidelines
Maintenance

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Cocoa 64103
LRV 21 | L* 52.91
V3 - Moderate Variation



Glow 64105
LRV 37.1 | L* 67.33



Parchment 64111
LRV 43.4 | L* 71.79
V2 - Slight Variation



Alabaster 64114
LRV 42.4 | L* 71.17
V3 - Moderate Variation



Buff 64140
LRV 28.3 | L* 60.17
V2 - Slight Variation




Nutshell 64150
LRV 12.6 | L* 42.09
V2 - Slight Variation

					
Ashen 64155 LRV 27 L* 59 V2 - Slight Variation	Bare 64200 LRV 39.1 L* 68.82 V2 - Slight Variation	Honey 64240 LRV 26 L* 58.01 V2 - Slight Variation	Fog 64327 LRV 17.8 L* 49.19 V3 - Moderate Variation	Alloy 64515 LRV 37.4 L* 67.56	Weathered 64518 LRV 29.5 L* 61.24 V2 - Slight Variation
					
Mercury 64530 LRV 25.5	Char 64549 LRV 7.1 V2 - Slight Variation	Cinder 64557 LRV 16.6 L* 47.78	Earthen 64710 LRV 10 L* 37.92 V3 - Moderate Variation	Bark 64720 LRV 12.5 L* 41.94 V2 - Slight Variation	Clove 64740 LRV 7.7 L* 33.32 V2 - Slight Variation
					
Chickory 64752 LRV 6.9 L* 31.68 V2 - Slight Variation	Russet 64760 LRV 7.4 L* 32.69 V2 - Slight Variation	Antler 64761 LRV 18.4 V2 - Slight Variation	Ginger 64820 LRV 15.2 L* 45.94 V2 - Slight Variation		

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1




Uniform Appearance

V2




Slight Variation

V3



Moderate Variation

V4



Substantial Variation