

## Grain Floating

Collection	<b>Grain + Pigment</b>	
Style Number	<b>0364V</b>	
Construction	<b>Heavy Comm Luxury Vinyl Tile W/ In*step Backing</b>	
Class / ASTM F1700	<b>Class III, Type B</b>	
Finish	<b>ExoGuard®</b>	
	U.s.	Metric
Nominal Dimensions	<b>7 in w x 48 in l</b>	<b>18 cm w x 121 cm l</b>
Actual Dimensions	<b>7.28 in w x 47.72 in l</b>	<b>18.49 cm w x 121.21 cm l</b>
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Thickness	<b>0.157 in</b>	<b>4 mm</b>
Edge Profile	<b>Micro-Bevel</b>	
Installation Type	<b>Click</b>	
Installation	<b>Floating</b>	

## Packaging

Pieces Per Carton	<b>10 pcs</b>	
Area Per Carton	<b>24.13 sq ft</b>	<b>2.24 sq m</b>
Weight Per Carton	<b>33.72 lbs</b>	<b>15.3 kg</b>



## Recommended Installation Method



Stagger

## Coordinating Products

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

## Performance + Testing

Residual Indentation (Astm F1914)	<b>Passes</b>
Resistance To Heat (Astm F1514)	<b>Passes</b>
Resistance To Light (Astm F1515)	<b>Passes</b>
Resistance To Chemicals (Astm F925)	<b>Passes</b>
Coefficient Of Friction (Astm D2407, Slip Resistance)	<b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified

CE Marking (EN 14041) | 3rd Party Certified

Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Installation Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Cocoa 64103	Glow 64105	Parchment 64111	Alabaster 64114	Buff 64140	Nutshell 64150
LRV 21	LRV 37.1	LRV 43.4	LRV 42.4	LRV 28.3	LRV 12.6
V3 - Moderate Variation		V2 - Slight Variation	V3 - Moderate Variation	V2 - Slight Variation	V2 - Slight Variation



Ashen 64155  
LRV 27  
V2 - Slight Variation



Bare 64200  
LRV 39.1  
V2 - Slight Variation



Honey 64240  
LRV 26  
V2 - Slight Variation



Fog 64327  
LRV 17.8  
V3 - Moderate Variation



Alloy 64515  
LRV 37.4



Weathered 64518  
LRV 29.5  
V2 - Slight Variation



Mercury 64530  
LRV 25.5



Char 64549  
LRV 7.1  
V2 - Slight Variation



Cinder 64557  
LRV 16.6



Earthen 64710  
LRV 10  
V3 - Moderate Variation



Bark 64720  
LRV 12.5  
V2 - Slight Variation



Clove 64740  
LRV 7.7  
V2 - Slight Variation



Chickory 64752  
LRV 6.9  
V2 - Slight Variation



Russet 64760  
LRV 7.4  
V2 - Slight Variation



Antler 64761  
LRV 18.4  
V2 - Slight Variation



Ginger 64820  
LRV 15.2  
V2 - Slight Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

