


Grain Floating

Colección	Grain + Pigment	
Número De Estilo	0364V	
Construcción	Lvt Comercial De Tráfico Severo Con Sistema De Base In*step	
clase	Class III, Type B	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensiones Reales	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.157 in	4 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating	
Embalaje		
Piezas Por Caja	10 pcs	
Área Por Caja	24.13 sq ft	2.24 sq m
Peso Por Caja	33.72 lbs	15.3 kg



Método De Instalación Recomendado



Productos Que Combinan

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes
Coeficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado

CE Marking (EN 14041) | Certificado Tercerizado

Country of Origin | Imported

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción  
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales

Crédito MR: Divulgación y optimización de productos de construcción  
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

Crédito EQ: Materiales de baja emisión  
Opción 1: Cálculos de categoría de producto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Installation Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Cocoa 64103 LRV 21 V3 - Moderate Variation	Glow 64105 LRV 37.1	Parchment 64111 LRV 43.4 V2 - Slight Variation	Alabaster 64114 LRV 42.4 V3 - Moderate Variation	Buff 64140 LRV 28.3 V2 - Slight Variation	Nutshell 64150 LRV 12.6 V2 - Slight Variation



Ashen 64155  
LRV 27  
V2 - Slight Variation



Bare 64200  
LRV 39.1  
V2 - Slight Variation



Honey 64240  
LRV 26  
V2 - Slight Variation



Fog 64327  
LRV 17.8  
V3 - Moderate Variation



Alloy 64515  
LRV 37.4



Weathered 64518  
LRV 29.5  
V2 - Slight Variation



Mercury 64530  
LRV 25.5



Char 64549  
LRV 7.1  
V2 - Slight Variation



Cinder 64557  
LRV 16.6



Earthen 64710  
LRV 10  
V3 - Moderate Variation



Bark 64720  
LRV 12.5  
V2 - Slight Variation



Clove 64740  
LRV 7.7  
V2 - Slight Variation



Chickory 64752  
LRV 6.9  
V2 - Slight Variation



Russet 64760  
LRV 7.4  
V2 - Slight Variation



Antler 64761  
LRV 18.4  
V2 - Slight Variation



Ginger 64820  
LRV 15.2  
V2 - Slight Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

