

Grain Floating

Collection	Grain + Pigment	
Numéro De Style	0364V	
Construction	Carreau De Vinyle De Luxe Heavy Comm Avec Support In*step	
classe	Class III, Type B	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensions Réelles	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.157 in	4 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating	

Emballage

Pièces Par Carton	10 pcs	
Surface Par Carton	24.13 sq ft	2.24 sq m
Poids Par Carton	33.72 lbs	15.3 kg



Méthodes d'Installation Conseillées



Stagger

Coordination Des Produits

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co₂/M²

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé

CE Marking (EN 14041) | Certifié Par Un Tiers

Country of Origin | Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulcation et optimisation des produits de construction

« Crédit MR : Divulcation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cocoa 64103 LRV 21 V3 - Moderate Variation	Glow 64105 LRV 37.1	Parchment 64111 LRV 43.4 V2 - Slight Variation	Alabaster 64114 LRV 42.4 V3 - Moderate Variation	Buff 64140 LRV 28.3 V2 - Slight Variation	Nutshell 64150 LRV 12.6 V2 - Slight Variation
					
Ashen 64155 LRV 27 V2 - Slight Variation	Bare 64200 LRV 39.1 V2 - Slight Variation	Honey 64240 LRV 26 V2 - Slight Variation	Fog 64327 LRV 17.8 V3 - Moderate Variation	Alloy 64515 LRV 37.4	Weathered 64518 LRV 29.5 V2 - Slight Variation

 Mercury 64530 LRV 25.5	 Char 64549 LRV 7.1 V2 - Slight Variation	 Cinder 64557 LRV 16.6	 Earthen 64710 LRV 10 V3 - Moderate Variation	 Bark 64720 LRV 12.5 V2 - Slight Variation	 Clove 64740 LRV 7.7 V2 - Slight Variation
 Chickory 64752 LRV 6.9 V2 - Slight Variation	 Russet 64760 LRV 7.4 V2 - Slight Variation	 Antler 64761 LRV 18.4 V2 - Slight Variation	 Ginger 64820 LRV 15.2 V2 - Slight Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

