

Grain Floating


コレクション	Grain + Pigment	
スタイルナンバー	0364V	
建設	「イン*ステップ」バックングを備えたヘビーコマ ーシャルラグジュアリービニールタイル	
クラス	Class III, Type B	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	7 in w x 48 in l	18 cm w x 121 cm l
実際の寸法	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.157 in	4 mm
エッジプロファイル	マイクロペベル	
Installation Type	Click	
インストール	Floating	

包装

ボックスあたりの個数	10 pcs	
ボックスあたりの面積	24.13 sq ft	2.24 sq m
ボックスあたりの重量	33.72 lbs	15.3 kg



推奨インストール方法



Stagger

コーディネート商品

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
摩擦係数(astm D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Embodied Carbon (Cradle to Gate)	7.31 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	
	FloorScore® 認証取得
	CE Marking (EN 14041) 第三者認証取得
	Country of Origin Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	Health Product Declaration (HPD) 100 Ppm Disclosure
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore Certified
Installation Guidelines	

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cocoa 64103 LRV 21 V3 - Moderate Variation	Glow 64105 LRV 37.1	Parchment 64111 LRV 43.4 V2 - Slight Variation	Alabaster 64114 LRV 42.4 V3 - Moderate Variation	Buff 64140 LRV 28.3 V2 - Slight Variation	Nutshell 64150 LRV 12.6 V2 - Slight Variation



Ashen 64155
LRV 27
V2 - Slight Variation



Bare 64200
LRV 39.1
V2 - Slight Variation



Honey 64240
LRV 26
V2 - Slight Variation



Fog 64327
LRV 17.8
V3 - Moderate Variation



Alloy 64515
LRV 37.4



Weathered 64518
LRV 29.5
V2 - Slight Variation



Mercury 64530
LRV 25.5



Char 64549
LRV 7.1
V2 - Slight Variation



Cinder 64557
LRV 16.6



Earthen 64710
LRV 10
V3 - Moderate Variation



Bark 64720
LRV 12.5
V2 - Slight Variation



Clove 64740
LRV 7.7
V2 - Slight Variation



Chickory 64752
LRV 6.9
V2 - Slight Variation



Russet 64760
LRV 7.4
V2 - Slight Variation



Antler 64761
LRV 18.4
V2 - Slight Variation



Ginger 64820
LRV 15.2
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

