

Grain Floating

수집	Grain + Pigment	
스타일 번호	0364V	
구성	"In*step"역행을 가진 헤비급 상업적인 고급 비닐 도와	
수업	Class III, Type B	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 48 in l	18 cm w x 121 cm l
실제 치수	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.157 in	4 mm
가장자리 프로필	마이크로 베벨	
Installation Type	Click	
설치	Floating	

포장

상자 당 조각	10 pcs	
상자 당 면적	24.13 sq ft	2.24 sq m
상자 당 무게	33.72 lbs	15.3 kg



권장 설치 방법



Stagger

코디네이팅 제품

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

공연 + 테스트

잔차 들어 쓰기 (Astm F1914)	Passes
내열성 (Astm F1514)	Passes
내광성 (Astm F1515)	Passes
화학 물질에 대한 내성 (Astm F925)	Passes
마찰 계수 (astm D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득

7.31 Kg Co₂/M²

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | 인증

CE Marking (EN 14041) | 타사 인증 획득

Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축
재료 성분-옵션 1 : 재료 성분보고

MR 크레딧 : 제품 공개 및 최적화 구축
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

EQ 크레딧 : 저 발광 재료
옵션 1 : 제품 범주 계산

Installation Guidelines

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Cocoa 64103 LRV 21 V3 - Moderate Variation</div>	 <div>Glow 64105 LRV 37.1</div>	 <div>Parchment 64111 LRV 43.4 V2 - Slight Variation</div>	 <div>Alabaster 64114 LRV 42.4 V3 - Moderate Variation</div>	 <div>Buff 64140 LRV 28.3 V2 - Slight Variation</div>	 <div>Nutshell 64150 LRV 12.6 V2 - Slight Variation</div>
 <div>Ashen 64155 LRV 27 V2 - Slight Variation</div>	 <div>Bare 64200 LRV 39.1 V2 - Slight Variation</div>	 <div>Honey 64240 LRV 26 V2 - Slight Variation</div>	 <div>Fog 64327 LRV 17.8 V3 - Moderate Variation</div>	 <div>Alloy 64515 LRV 37.4</div>	 <div>Weathered 64518 LRV 29.5 V2 - Slight Variation</div>



Mercury 64530
LRV 25.5



Char 64549
LRV 7.1
V2 - Slight Variation



Cinder 64557
LRV 16.6



Earthen 64710
LRV 10
V3 - Moderate Variation



Bark 64720
LRV 12.5
V2 - Slight Variation



Clove 64740
LRV 7.7
V2 - Slight Variation



Chickory 64752
LRV 6.9
V2 - Slight Variation



Russet 64760
LRV 7.4
V2 - Slight Variation



Antler 64761
LRV 18.4
V2 - Slight Variation



Ginger 64820
LRV 15.2
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

