

Grain Floating

Coleção	Grain + Pigment	
Número Do Produto	0364V	
Construção	Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step	
classe	Class III, Type B	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 121 cm l
Dimensões Reais	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.157 in	4 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating	

Empacotamento

Peças Por Caixa	10 pcs	
Área Por Caixa	24.13 sq ft	2.24 sq m
Peso Por Caixa	33.72 lbs	15.3 kg



Método De Instalação Recomendado



Stagger

Produtos Coordenados

LVT: Pigment Floating, Grain Direct Glue, Pigment Direct Glue

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)

Atributos + Certificações

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co₂/M²

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado

CE Marking (EN 14041) | Certificado 3rd Party

Country of Origin | Imported

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais

MR Credit: Divulgação e otimização de produtos de construção
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)

Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

[Installation Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cocoa 64103	Glow 64105	Parchment 64111	Alabaster 64114	Buff 64140	Nutshell 64150
LRV 21	LRV 37.1	LRV 43.4	LRV 42.4	LRV 28.3	LRV 12.6
V3 - Moderate Variation		V2 - Slight Variation	V3 - Moderate Variation	V2 - Slight Variation	V2 - Slight Variation



Ashen 64155
LRV 27

V2 - Slight Variation



Bare 64200
LRV 39.1

V2 - Slight Variation



Honey 64240
LRV 26

V2 - Slight Variation



Fog 64327
LRV 17.8

V3 - Moderate Variation



Alloy 64515
LRV 37.4

Weathered 64518
LRV 29.5

V2 - Slight Variation



Mercury 64530
LRV 25.5



Char 64549
LRV 7.1

V2 - Slight Variation



Cinder 64557
LRV 16.6



Earthen 64710
LRV 10

V3 - Moderate Variation



Bark 64720
LRV 12.5

V2 - Slight Variation



Clove 64740
LRV 7.7

V2 - Slight Variation



Chickory 64752
LRV 6.9

V2 - Slight Variation



Russet 64760
LRV 7.4

V2 - Slight Variation



Antler 64761
LRV 18.4

V2 - Slight Variation



Ginger 64820
LRV 15.2

V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

