


Stratum 500

| | | |
|---------------------------|--|--------------------------|
| Collection | Stratum | |
| Style Number | 023UV | |
| Construction | Multilayer WPC With Attached Cork Underlayment | |
| class | Class III, Type B | |
| Attached Underlayment | Cork | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Nominal Dimensions | 5 in w x 48 in l | 13 cm w x 122 cm l |
| Actual Dimensions | 4.96 in w x 48.03 in l | 12.60 cm w x 122.00 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Product Thickness | 0.315 in | 8 mm |
| Edge Profile | Micro-Bevel | |
| Installation Type | Click | |
| Installation | Floating Or Direct Glue | |
| Recommended Adhesive | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL | |

Packaging

| | | |
|----------------|-------------|-----------|
| Pieces Per Box | 16 pcs | |
| Area Per Box | 26.47 sq ft | 2.46 sq m |
| Weight Per Box | 44.09 lbs | 20 kg |

Recommended Installation Method



Coordinating Products

None: Stratum 1200
COREtec: Stratum 700, Stratum XI, Stratum Eiris, Stratum Linear, Defined



Performance + Testing

| | |
|--|---|
| Residual Indentation (Astm F1914) | Passes |
| Resistance To Heat (Astm F1514) | Passes |
| Resistance To Light (Astm F1515) | Passes |
| Resistance To Chemicals (Astm F925) | Passes |
| Radiant Panel (Astm E648) | Passes, Class I |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | |

Warranties

15 Year Commercial Limited

Attributes + Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin China |

Green Leed Contribution Credit










| | |
|---|--|
| MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting | Health Product Declaration (HPD) 100 Ppm Disclosure |
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials Option 1: Product Category Calculations | FloorScore Certified |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |
| Maintenance Guidelines | |

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|---|---|---|
|  <div>Acacia 00201 V4 - Substantial Variation</div> |  <div>Mocha Oak 00202 V3 - Moderate Variation</div> |  <div>Vintage Oak 00205 V2 - Slight Variation</div> |  <div>Weathered Oak 00206 V3 - Moderate Variation</div> |  <div>Limerick Oak 00207 V3 - Moderate Variation</div> |  <div>Apalachicola Pine 00501 V4 - Substantial Variation</div> |
|  <div>Targhee Walnut 00503 V1 - Uniform Appearance</div> |  <div>Chattahoochee Oak 00504 V4 - Substantial Variation</div> |  <div>Allegheny Maple 00505 V4 - Substantial Variation</div> |  <div>Wimena Pine 00506 V2 - Slight Variation</div> |  <div>Oconee Walnut 00507 V4 - Substantial Variation</div> |  <div>Gallatin Hickory 00508 V4 - Substantial Variation</div> |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

