


## Stratum 500

Coleção	<b>Stratum</b>	
Número Do Produto	<b>023UV</b>	
Construção	<b>WPC Multicamada Com Camada De Cortiça Anexada</b>	
classe	<b>Class III, Type B</b>	
Manta Inferior Adicional	<b>Cortiça</b>	
Acabamento	<b>ExoGuard®</b>	
	U.s.	Metric
Dimensões Nominais	<b>5 in w x 48 in l</b>	<b>13 cm w x 122 cm l</b>
Dimensões Reais	<b>4.96 in w x 48.03 in l</b>	<b>12.60 cm w x 122.00 cm l</b>
Espessura Da Camada De Uso	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Espessura Total Do Produto	<b>0.315 in</b>	<b>8 mm</b>
Perfil De Borda	<b>Micro-Chanfrado</b>	
Installation Type	<b>Click</b>	
Instalação	<b>Floating Or Direct Glue</b>	
Adesivo Recomendado	<b>4200 1 Gallon, 4200 4 Gallon, 2200 4 Gallon, 2200 1 Gallon or 4151</b>	

### Empacotamento

Peças Por Caixa	<b>16 pcs</b>	
Área Por Caixa	<b>26.47 sq ft</b>	<b>2.46 sq m</b>
Peso Por Caixa	<b>44.09 lbs</b>	<b>20 kg</b>

### Método De Instalação Recomendado



### Produtos Coordenados

COREtec: Stratum 700, Stratum XI, Stratum Eiris, Defined

### desempenho + teste

recuo residual (ASTM F1914)	<b>Passes</b>
resistência ao calor (ASTM F1514)	<b>Passes</b>
resistência à luz (ASTM F1515)	<b>Passes</b>
resistência a produtos químicos (ASTM F925)	<b>Passes</b>
painel radiante (ASTM E648)	<b>Passes, Class I</b>
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.



Garantias

[10 Year Light Commercial Limited Warranty](#)

Atributos + Certificações

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certificado  
Greenguard Gold | Certificado

Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017  
11.2 Kg Co<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

**Absence of Asbestos**  
**Absence of Heavy Metals**  
**Absence of Halogenated Flame Retardants**  
  
**Ortho-Phthalates**  
**Greenguard Gold Certificate**

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção  
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais  
MR Credit: Divulgação e otimização de produtos de construção  
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)  
Crédito de EQ: Materiais de baixa emissão  
Opção 1: cálculos de categoria de produto

**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore & Greenguard Gold Certified**

[Installation Guidelines](#)








Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Acacia 00201 V2 - Slight Variation	Mocha Oak 00202 V3 - Moderate Variation	Vintage Oak 00205 V2 - Slight Variation	Weathered Oak 00206 V3 - Moderate Variation	Limerick Oak 00207 V3 - Moderate Variation	Apalachicola Pine 00501 V4 - Substantial Variation
					
Targhee Walnut 00503 V1 - Uniform Appearance	Chattahoochee Oak 00504 V4 - Substantial Variation	Allegheny Maple 00505 V4 - Substantial Variation	Wimena Pine 00506 V2 - Slight Variation	Oconee Walnut 00507 V4 - Substantial Variation	Gallatin Hickory 00508 V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

