

Stratum 500


Coleção	Stratum	
Número Do Produto	023UV	
Construção	WPC Multicamada Com Camada De Cortiça Anexada	
classe	Class III, Type B	
Manta Inferior Adicional	Cortiça	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	5 in w x 48 in l	13 cm w x 122 cm l
Dimensões Reais	4.96 in w x 48.03 in l	12.60 cm w x 122.00 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.315 in	8 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating Or Direct Glue	
Adesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	



Empacotamento

Peças Por Caixa	16 pcs	
Área Por Caixa	26.47 sq ft	2.46 sq m
Peso Por Caixa	44.09 lbs	20 kg

Método De Instalação Recomendado



Produtos Coordenados

None: Stratum 1200
COREtec: Stratum 700, Stratum XI, Stratum Eiris, Stratum Linear, Defined

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I
Coeficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garantias

15 Anos Comercial Limitada










Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.
Maintenance Guidelines	

Available Colorways

 <div>Acacia 00201 V4 - Substantial Variation</div>	 <div>Mocha Oak 00202 V3 - Moderate Variation</div>	 <div>Vintage Oak 00205 V2 - Slight Variation</div>	 <div>Weathered Oak 00206 V3 - Moderate Variation</div>	 <div>Limerick Oak 00207 V3 - Moderate Variation</div>	 <div>Apalachicola Pine 00501 V4 - Substantial Variation</div>
 <div>Targhee Walnut 00503 V1 - Uniform Appearance</div>	 <div>Chattahoochee Oak 00504 V4 - Substantial Variation</div>	 <div>Allegheny Maple 00505 V4 - Substantial Variation</div>	 <div>Wimena Pine 00506 V2 - Slight Variation</div>	 <div>Oconee Walnut 00507 V4 - Substantial Variation</div>	 <div>Gallatin Hickory 00508 V4 - Substantial Variation</div>

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

