

Stratum 500


Colección	Stratum	
Número De Estilo	023UV	
Construcción	WPC Multicapa Con Base De Corcho Adjunta	
clase	Class III, Type B	
Manta Inferior Adicional	Corcho	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	5 in w x 48 in l	13 cm w x 122 cm l
Dimensiones Reales	4.96 in w x 48.03 in l	12.60 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.315 in	8 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

Embalaje

Piezas Por Caja	16 pcs	
Área Por Caja	26.47 sq ft	2.46 sq m
Peso Por Caja	44.09 lbs	20 kg



Método De Instalación Recomendado



Productos Que Combinan

None: Stratum 1200
COREtec: Stratum 700, Stratum XI, Stratum Eiris, Stratum Linear, Defined

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes
Coeficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garantías

15 Años Limitado A Uso Comercial








Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® Certificado Greenguard (Certification, Gold, Private Label) Certificado Country of Origin China

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales	Health Product Declaration (HPD) 100 Ppm Disclosure
Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore & Greenguard Gold Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.
Maintenance Guidelines	

Available Colorways

					
Acacia 00201 V4 - Substantial Variation	Mocha Oak 00202 V3 - Moderate Variation	Vintage Oak 00205 V2 - Slight Variation	Weathered Oak 00206 V3 - Moderate Variation	Limerick Oak 00207 V3 - Moderate Variation	Apalachicola Pine 00501 V4 - Substantial Variation
					
Targhee Walnut 00503 V1 - Uniform Appearance	Chattahoochee Oak 00504 V4 - Substantial Variation	Allegheny Maple 00505 V4 - Substantial Variation	Wimena Pine 00506 V2 - Slight Variation	Oconee Walnut 00507 V4 - Substantial Variation	Gallatin Hickory 00508 V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

