


Stratum 700

수집	Stratum	
스타일 번호	024UV	
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(WPC)	
수업	Class III, Type B	
첨부 된 밀 갈개	코르크	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 48 in l	18 cm w x 122 cm l
실제 치수	7.13 in w x 48.03 in l	18.11 cm w x 122.00 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.315 in	8 mm
가장자리 프로필	마이크로 베벨	
Installation Type	Click	
설치	Floating Or Direct Glue	
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

포장

상자 당 조각	16 pcs	
상자 당 면적	38.03 sq ft	3.53 sq m
상자 당 무게	63.05 lbs	28.6 kg

권장 설치 방법



코디네이팅 제품

COREtec: Stratum 500, Stratum XI, Stratum Eiris, Stratum Linear, Defined, Stratum Nordic



공연 + 테스트

잔차 들어 쓰기 (Astm F1914)	Passes
내열성 (Astm F1514)	Passes
내광성 (Astm F1515)	Passes
화학 물질에 대한 내성 (Astm F925)	Passes
복사 패넬 (Astm E648)	Passes, Class I
마찰 계수(astm D2407, 미끄러짐 저항)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

보증

15년 상용 제한

속성 + 인증

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® 인증
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축 재료 성분-옵션 1 : 재료 성분보고	Health Product Declaration (HPD) 100 Ppm Disclosure
MR 크레딧 : 제품 공개 및 최적화 구축 환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ 크레딧 : 저 발광 재료 옵션 1 : 제품 범주 계산	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
Maintenance Guidelines	

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cerused Oak 00210 LRV 9.9 L* 37.66 V2 - Slight Variation	Monterey Oak 00211 LRV 23.4 L* 55.44 V2 - Slight Variation	Gifford Oak 00703 LRV 11 L* 39.5 V3 - Moderate Variation	Hoosier Oak 00704 LRV 15.4 L* 46.19 V2 - Slight Variation	Inyo Oak 00705 LRV 42.3 L* 71.1 V3 - Moderate Variation	Sawtooth Oak 00706 LRV 16.5 L* 47.57 V4 - Substantial Variation
					
Willamette Oak 00707 LRV 31.6 L* 62.98 V4 - Substantial Variation	Prescott Oak 00708 LRV 16.9 L* 48.14 V4 - Substantial Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

