

## Stratum 700


Coleção	<b>Stratum</b>	
Número Do Produto	<b>024UV</b>	
Construção	<b>WPC Multicamada Com Camada De Cortiça Anexada</b>	
classe	<b>Class III, Type B</b>	
Manta Inferior Adicional	<b>Cortiça</b>	
Acabamento	<b>ExoGuard®</b>	
	U.s.	Metric
Dimensões Nominais	<b>7 in w x 48 in l</b>	<b>18 cm w x 122 cm l</b>
Dimensões Reais	<b>7.13 in w x 48.03 in l</b>	<b>18.11 cm w x 122.00 cm l</b>
Espessura Da Camada De Uso	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Espessura Total Do Produto	<b>0.315 in</b>	<b>8 mm</b>
Perfil De Borda	<b>Micro-Chanfrado</b>	
Installation Type	<b>Click</b>	
Instalação	<b>Floating Or Direct Glue</b>	
Adesivo Recomendado	<b>, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL</b>	



### Empacotamento

Peças Por Caixa	<b>16 pcs</b>	
Área Por Caixa	<b>38.03 sq ft</b>	<b>3.53 sq m</b>
Peso Por Caixa	<b>63.05 lbs</b>	<b>28.6 kg</b>

### Método De Instalação Recomendado



### Produtos Coordenados

COREtec: Stratum 500, Stratum XI, Stratum Eiris, Stratum Linear, Defined

desempenho + teste

recuo residual (ASTM F1914)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
painel radiante (ASTM E648)	Passes, Class I
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.2 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   China


WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard Gold Certificate

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	Health Product Declaration (HPD)   100 Ppm Disclosure
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	FloorScore® Certified
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

## Available Colorways



Cerused Oak 00210  
LRV 9.9 | L\* 37.66  
V2 - Slight Variation



Monterey Oak 00211  
LRV 23.4 | L\* 55.44  
V2 - Slight Variation



Gifford Oak 00703  
LRV 11 | L\* 39.5  
V3 - Moderate Variation



Hoosier Oak 00704  
LRV 15.4 | L\* 46.19  
V2 - Slight Variation



Inyo Oak 00705  
LRV 42.3 | L\* 71.1  
V3 - Moderate Variation



Sawtooth Oak 00706  
LRV 16.5 | L\* 47.57  
V4 - Substantial Variation



Willamette Oak 00707  
LRV 31.6 | L\* 62.98  
V4 - Substantial Variation



Prescott Oak 00708  
LRV 16.9 | L\* 48.14  
V4 - Substantial Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

