


Stratum 700

Collection	Stratum		
Style Number	024UV		
Construction	Multilayer WPC With Attached Cork Underlayment		
Class / ASTM F3261	Class III, Type B		
Attached Underlayment	Cork		
Finish	ExoGuard®		
Nominal Dimensions	U.S.	Metric	
	7 in w x 48 in l	18 cm w x 122 cm l	
	Actual Dimensions	7.13 in w x 48.03 in l	18.11 cm w x 122.00 cm l
	Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
	Overall Thickness	0.315 in	8 mm
	Edge Profile	Micro-Bevel	
	Installation Type	Click	
Installation	Floating Or Direct Glue		
Recommended Adhesive	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL		

Packaging

Pieces per Carton	16 pcs	
Area per Carton	38.03 sq ft	3.53 sq m
Weight per Carton	63.49 lbs	28.8 kg

Recommended Installation Method



Coordinating Products

None: Stratum 1200
COREtec: Stratum 500, Stratum XI, Stratum Eiris, Stratum Linear, Defined

Warranties

[15 Year Commercial Limited Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Faimess pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend**** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	Greenguard Gold Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Installation Guidelines	
Maintenance Guidelines	

Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cerused Oak 00210 LRV 9.9 L* 37.66 V2 - Slight Variation	Monterey Oak 00211 LRV 23.4 L* 55.44 V2 - Slight Variation	Gifford Oak 00703 LRV 11 L* 39.5 V3 - Moderate Variation	Hoosier Oak 00704 LRV 15.4 L* 46.19 V2 - Slight Variation	Inyo Oak 00705 LRV 42.3 L* 71.1 V3 - Moderate Variation	Sawtooth Oak 00706 LRV 16.5 L* 47.57 V4 - Substantial Variation
					
Willamette Oak 00707 LRV 31.6 L* 62.98 V4 - Substantial Variation	Prescott Oak 00708 LRV 16.9 L* 48.14 V4 - Substantial Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

