

Stratum 700


Collection	Stratum	
Numéro De Style	024UV	
Construction	WPC Multicouche Avec Sous-Couche EN Liège Attachée	
classe	Class III, Type B	
Endos Intégrée	Liège	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensions Réelles	7.13 in w x 48.03 in l	18.11 cm w x 122.00 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.315 in	8 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Adhésif Recommandé	4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	



Emballage

Pièces Par Carton	16 pcs	
Surface Par Carton	38.03 sq ft	3.53 sq m
Poids Par Carton	63.49 lbs	28.8 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

COREtec: Stratum 500, Stratum XI, Stratum Eiris, Defined

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	Greenguard Gold Agréé
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.2 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt	Absence of Heavy Metals
X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt	Absence of Halogenated Flame Retardants
Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt	Ortho-Phthalates
X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt	Greenguard Gold Certificate

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgation et optimisation des produits de construction	Health Product Declaration (HPD) 100 Ppm Disclosure
« Crédit MR : Divulgation et optimisation des produits de construction	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédit EQ : matériaux faibles émissions	Greenguard Gold Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cerused Oak 00210	Monterey Oak 00211	Gifford Oak 00703	Hoosier Oak 00704	Inyo Oak 00705	Sawtooth Oak 00706
LRV 9.9 L* 37.66	LRV 23.4 L* 55.44	LRV 11 L* 39.5	LRV 15.4 L* 46.19	LRV 42.3 L* 71.1	LRV 16.5 L* 47.57
V2 - Slight Variation	V2 - Slight Variation	V3 - Moderate Variation	V2 - Slight Variation	V3 - Moderate Variation	V4 - Substantial Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

