

Stratum 700


|                           |  |                          |
|---------------------------|--|--------------------------|
| Collection                | Stratum  |                          |
| Style Number              | 024UV  |                          |
| Construction              | Multilayer WPC With Attached Cork Underlayment   |                          |
| class                     | Class III, Type B  |                          |
| Attached Underlayment     | Cork   |                          |
| Finish                    | ExoGuard®  |                          |
|                           | U.s.   | Metric                   |
| Nominal Dimensions        | 7 in w x 48 in l   | 18 cm w x 122 cm l       |
| Actual Dimensions         | 7.13 in w x 48.03 in l   | 18.11 cm w x 122.00 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)   | 0.51 mm                  |
| Overall Product Thickness | 0.315 in   | 8 mm                     |
| Edge Profile              | Micro-Bevel  |                          |
| Installation Type         | Click  |                          |
| Installation              | Floating Or Direct Glue  |                          |
| Recommended Adhesive      | 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL |                          |

Packaging

|                |             |           |
|----------------|-------------|-----------|
| Pieces Per Box | 16 pcs      |           |
| Area Per Box   | 38.03 sq ft | 3.53 sq m |
| Weight Per Box | 63.05 lbs   | 28.6 kg   |



Recommended Installation Method



Coordinating Products

None: Stratum 1200  
COREtec: Stratum 500, Stratum XI, Stratum Eiris, Stratum Linear, Defined

Performance + Testing

|  |   |
|--|---|
| Residual Indentation (Astm F1914)  | Passes  |
| Resistance To Heat (Astm F1514)  | Passes  |
| Resistance To Light (Astm F1515)   | Passes  |
| Resistance To Chemicals (Astm F925)  | Passes  |
| Coefficient Of Friction (Astm D2407, Slip Resistance)  | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. |   |

Warranties

15 Year Commercial Limited


Attributes + Certifications

|   |   |
|---|---|
| Health & Wellbeing                      |   |
| Material Ingredient Transparency        | Health Product Declaration (HPD)   1000 ppm Disclosure  |
| Climate Impact                          |   |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)   |
| Global Product Assessment               | FloorScore®   Certified<br>Greenguard (Certification, Gold, Private Label)   Certified<br>Country of Origin   China |

Green Leed Contribution Credit

|   |  |
|---|--|
| MR Credit: Building Product Disclosure and Optimization<br>Material Ingredients - Option 1: Material Ingredient Reporting                         | Health Product Declaration (HPD)   100 Ppm Disclosure  |
| MR Credit: Building Product Disclosure and Optimization<br>Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017   |
| EQ Credit: Low Emitting Materials<br>Option 1: Product Category Calculations  | FloorScore & Greenguard Gold Certified   |
| Installation Guidelines   | Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.<br>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br>*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.<br><br>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
| Maintenance Guidelines  |  |

## Available Colorways



Cerused Oak 00210  
LRV 9.9  
V2 - Slight Variation



Monterey Oak 00211  
LRV 23.4  
V2 - Slight Variation



Gifford Oak 00703  
LRV 11  
V3 - Moderate Variation



Hoosier Oak 00704  
LRV 15.4  
V2 - Slight Variation



Inyo Oak 00705  
LRV 42.3  
V3 - Moderate Variation



Sawtooth Oak 00706  
LRV 16.5  
V4 - Substantial Variation



Willamette Oak 00707  
LRV 31.6  
V4 - Substantial Variation



Prescott Oak 00708  
LRV 16.9  
V4 - Substantial Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

