

Stratum 700


コレクション	Stratum	
スタイルナンバー	024UV	
建設	コルク下敷を含む多層WPC	
クラス	Class III, Type B	
付属下敷	コルク	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	7 in w x 48 in l	18 cm w x 122 cm l
実際の寸法	7.13 in w x 48.03 in l	18.11 cm w x 122.00 cm l
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.315 in	8 mm
エッジプロファイル	マイクロベベル	
Installation Type	Click	
インストール	Floating Or Direct Glue	
推奨接着剤	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

包装

ボックスあたりの個数	16 pcs	
ボックスあたりの面積	38.03 sq ft	3.53 sq m
ボックスあたりの重量	63.05 lbs	28.6 kg



推奨インストール方法



コーディネート商品

COREtec: Stratum 500, Stratum XI, Stratum Eiris, Stratum Linear, Defined, Stratum Nordic

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® 認証取得 Greenguard (Certification, Gold, Private Label) 認証取得 Country of Origin 中国

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	Health Product Declaration (HPD) 100 Ppm Disclosure
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore & Greenguard Gold Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

					
Cerused Oak 00210 LRV 9.9 V2 - Slight Variation	Monterey Oak 00211 LRV 23.4 V2 - Slight Variation	Gifford Oak 00703 LRV 11 V3 - Moderate Variation	Hoosier Oak 00704 LRV 15.4 V2 - Slight Variation	Inyo Oak 00705 LRV 42.3 V3 - Moderate Variation	Sawtooth Oak 00706 LRV 16.5 V4 - Substantial Variation
					
Willamette Oak 00707 LRV 31.6 V4 - Substantial Variation	Prescott Oak 00708 LRV 16.9 V4 - Substantial Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

