

Stratum Eiris


Colección	Stratum	
Número De Estilo	053UV	
Construcción	WPC Multicapa Con Base De Corcho Adjunta	
clase	Class III, Type B	
Manta Inferior Adicional	Corcho	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 59 in l	18 cm w x 150 cm l
Dimensiones Reales	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
Desgaste De La Capa De Uso	30 mil (0.03 in)	0.76 mm
Espesor Total Del Producto	0.335 in	8.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	



Embalaje

Piezas Por Caja	6 pcs	
Área Por Caja	17.43 sq ft	1.62 sq m
Peso Por Caja	33.95 lbs	15.4 kg

Método De Instalación Recomendado



Productos Que Combinan

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.5 Kg Co ₂ /M ²
Total Recycled Content	41% (Pre-Consumer 41% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard Gold Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales	Health Product Declaration (HPD) 100 Ppm Disclosure
Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified

[Installation Guidelines](#)


Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways




Cinnamon 06001
LRV 14.9 | L* 45.47
V3 - Moderate Variation




Tannery Brown 06002
LRV 10.3 | L* 38.4
V2 - Slight Variation




Summer Truffle 06003
LRV 9.2 | L* 36.34
V2 - Slight Variation




Abyss 06004
LRV 6.6 | L* 30.97
V3 - Moderate Variation




Ivory 06005
LRV 25.4 | L* 57.48
V2 - Slight Variation



Bone 06006
LRV 23 | L* 55.05
V4 - Substantial Variation



Morchella 06007
LRV 9.5 | L* 36.84
V2 - Slight Variation



Cremini 06008
LRV 35.6 | L* 66.23
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

