

Stratum Eiris


Collection	Stratum	
Numéro De Style	053UV	
Construction	WPC Multicouche Avec Sous-Couche EN Liège Attachée	
classe	Class III, Type B	
Endos Intégrée	Liège	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 59 in l	18 cm w x 150 cm l
Dimensions Réelles	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
Épaisseur De La Couche d'Usure	30 mil (0.03 in)	0.76 mm
Épaisseur Générale Du Produit	0.335 in	8.5 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Adhésif Recommandé	4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	



Emballage

Pièces Par Carton	6 pcs	
Surface Par Carton	17.43 sq ft	1.62 sq m
Poids Par Carton	33.95 lbs	15.4 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

COREtec: Stratum 500, Stratum 700, Stratum XI, Defined

performance + Tests et essai

poinçonnement rémanent (ASTM F1914)	Passes
résistance à la chaleur (ASTM F1514)	Passes
résistance à la lumière (ASTM F1515)	Passes
résistance chimique (ASTM F925)	Passes
Essai au panneau radiant (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Garanties

[Limitée Commerciale De 15 Ans](#)

## Attributs + Certifications

## Health &amp; Wellbeing

Material Ingredient Transparency

Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure

FloorScore® | Agréé

Greenguard Gold | Agréé

## Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025,  
EN 15804 Et ISO 21930:2017

Embodied Carbon (Cradle to Gate)

11.5 Kg CO<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

41% (Pre-Consumer 41% | Post-Consumer 0%)

## Global Product Assessment

Country of Origin | Imported

## WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

**Absence of Asbestos**

X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt

**Absence of Heavy Metals**

X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt

**Absence of Halogenated Flame Retardants**

Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt

**Ortho-Phthalates**

X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

**Greenguard Gold Certificate**

## Contribution Au Certificat Vert Leed

« Crédit MR : Divulcation et optimisation des produits de construction

**Health Product Declaration (HPD) | 100 Ppm Disclosure**

« Crédit MR : Divulcation et optimisation des produits de construction

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

Crédit EQ : matériaux faibles émissions

**FloorScore & Greenguard Gold Certified**[Installation Guidelines](#)Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



Cinnamon 06001  
LRV 14.9 | L\* 45.47  
V3 - Moderate Variation



Tannery Brown 06002  
LRV 10.3 | L\* 38.4  
V2 - Slight Variation



Summer Truffle 06003  
LRV 9.2 | L\* 36.34  
V2 - Slight Variation



Abyss 06004  
LRV 6.6 | L\* 30.97  
V3 - Moderate Variation



Ivory 06005  
LRV 25.4 | L\* 57.48  
V2 - Slight Variation



Bone 06006  
LRV 23 | L\* 55.05  
V4 - Substantial Variation



Morchella 06007  
LRV 9.5 | L\* 36.84  
V2 - Slight Variation



Cremini 06008  
LRV 35.6 | L\* 66.23  
V3 - Moderate Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

