

Stratum Eiris


Collection	Stratum	
Numéro De Style	053UV	
Construction	WPC Multicouche Avec Sous-Couche EN Liège Attachée	
classe	Class III, Type B	
Endos Intégrée	Liège	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 59 in l	18 cm w x 150 cm l
Dimensions Réelles	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
Épaisseur De La Couche d'Usure	30 mil (0.03 in)	0.76 mm
Épaisseur Générale Du Produit	0.335 in	8.5 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Adhésif Recommandé	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	



Emballage

Pièces Par Carton	6 pcs	
Surface Par Carton	17.43 sq ft	1.62 sq m
Poids Par Carton	33.95 lbs	15.4 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

None: Stratum 1200  
COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Essai Au Panneau Radiant (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Agréé

Climate Impact

Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Total Recycled Content	41% (Pre-Consumer 41%   Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

Contribution Au Certificat Vert Leed

- « Crédit MR : Divulgation et optimisation des produits de construction
- « Crédit MR : Divulgation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)  
[Maintenance Guidelines](#)








**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Cinnamon 06001 LRV 14.9   L* 45.47 V3 - Moderate Variation	Tannery Brown 06002 LRV 10.3   L* 38.4 V2 - Slight Variation	Summer Truffle 06003 LRV 9.2   L* 36.34 V2 - Slight Variation	Abyss 06004 LRV 6.6   L* 30.97 V3 - Moderate Variation	Ivory 06005 LRV 25.4   L* 57.48 V2 - Slight Variation	Bone 06006 LRV 23   L* 55.05 V4 - Substantial Variation
					
Morchella 06007 LRV 9.5   L* 36.84 V2 - Slight Variation	Cremini 06008 LRV 35.6   L* 66.23 V3 - Moderate Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

