

## Stratum Eiris


コレクション	Stratum	
スタイルナンバー	053UV	
建設	コルク下敷を含む多層WPC	
クラス	Class III, Type B	
付属下敷	コルク	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	7 in w x 59 in l	18 cm w x 150 cm l
実際の寸法	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
摩耗層の厚さ	30 mil (0.03 in)	0.76 mm
製品全体の厚さ	0.335 in	8.5 mm
エッジプロファイル	マイクロベベル	
Installation Type	Click	
インストール	Floating Or Direct Glue	
推奨接着剤	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	



### 包装

ボックスあたりの個数	<b>6 pcs</b>	
ボックスあたりの面積	<b>17.43 sq ft</b>	<b>1.62 sq m</b>
ボックスあたりの重量	<b>33.95 lbs</b>	<b>15.4 kg</b>

### 推奨インストール方法



### コーディネート商品

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined, Stratum Nordic

### パフォーマンス + テスト

残留圧痕 (ASTM F1914)	<b>Passes</b>
耐熱性 (ASTM F1514)	<b>Passes</b>
耐光性 (ASTM F1515)	<b>Passes</b>
耐薬品性 (ASTM F925)	<b>Passes</b>
放射パネル (ASTM E648)	<b>Passes, Class I</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   認証取得
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Embodied Carbon (Cradle to Gate)	11.5 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	41% (Pre-Consumer 41%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   中国

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>Greenguard Gold Certificate</b>

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	<b>FloorScore® Certified</b>

Installation Guidelines


Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways




Cinnamon 06001  
LRV 14.9 | L\* 45.47  
V3 - Moderate Variation




Tannery Brown 06002  
LRV 10.3 | L\* 38.4  
V2 - Slight Variation




Summer Truffle 06003  
LRV 9.2 | L\* 36.34  
V2 - Slight Variation




Abyss 06004  
LRV 6.6 | L\* 30.97  
V3 - Moderate Variation




Ivory 06005  
LRV 25.4 | L\* 57.48  
V2 - Slight Variation



Bone 06006  
LRV 23 | L\* 55.05  
V4 - Substantial Variation



Morchella 06007  
LRV 9.5 | L\* 36.84  
V2 - Slight Variation



Cremini 06008  
LRV 35.6 | L\* 66.23  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

