

Stratum Eiris


수집	Stratum	
스타일 번호	053UV	
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(WPC)	
수업	Class III, Type B	
첨부 된 밀 갈개	코르크	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 59 in l	18 cm w x 150 cm l
실제 치수	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
마모 층 두께	30 mil (0.03 in)	0.76 mm
전체 제품 두께	0.335 in	8.5 mm
가장자리 프로파일	마이크로 베벨	
Installation Type	Click	
설치	Floating Or Direct Glue	
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	



포장

상자 당 조각	6 pcs	
상자 당 면적	17.43 sq ft	1.62 sq m
상자 당 무게	33.95 lbs	15.4 kg

권장 설치 방법



코디네이팅 제품

COREtec: Stratum 500, Stratum 700, Stratum XI, Defined, Stratum Nordic

공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
화학 물질에 대한 내성 (ASTM F925)	Passes
복사 패널 (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

[15년 상용 제한](#)

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency

Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure

FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득

11.5 Kg Co₂/M²

41% (Pre-Consumer 41% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt

X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt

X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos**Absence of Heavy Metals****Absence of Halogenated Flame Retardants****Ortho-Phthalates****Greenguard Gold Certificate**

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축

재료 성분-옵션 1 : 재료 성분보고

MR 크레딧 : 제품 공개 및 최적화 구축

환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

EQ 크레딧 : 저 발광 재료

옵션 1 : 제품 범주 계산

Health Product Declaration (HPD) | 100 Ppm Disclosure**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017****FloorScore® Certified**[Installation Guidelines](#)[Maintenance Guidelines](#)Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways




Cinnamon 06001
LRV 14.9 | L* 45.47
V3 - Moderate Variation



Tannery Brown 06002
LRV 10.3 | L* 38.4
V2 - Slight Variation



Summer Truffle 06003
LRV 9.2 | L* 36.34
V2 - Slight Variation



Abyss 06004
LRV 6.6 | L* 30.97
V3 - Moderate Variation



Ivory 06005
LRV 25.4 | L* 57.48
V2 - Slight Variation



Bone 06006
LRV 23 | L* 55.05
V4 - Substantial Variation



Morchella 06007
LRV 9.5 | L* 36.84
V2 - Slight Variation



Cremini 06008
LRV 35.6 | L* 66.23
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

