

Stratum Eiris


Coleção	Stratum	
Número Do Produto	053UV	
Construção	WPC Multicamada Com Camada De Cortiça Anexada	
classe	Class III, Type B	
Manta Inferior Adicional	Cortiça	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 59 in l	18 cm w x 150 cm l
Dimensões Reais	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
Espessura Da Camada De Uso	30 mil (0.03 in)	0.76 mm
Espessura Total Do Produto	0.335 in	8.5 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating Or Direct Glue	
Adesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	



Empacotamento

Peças Por Caixa	6 pcs	
Área Por Caixa	17.43 sq ft	1.62 sq m
Peso Por Caixa	33.95 lbs	15.4 kg

Método De Instalação Recomendado



Produtos Coordenados

None: Stratum 1200  
COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	41% (Pre-Consumer 41%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   China

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	Health Product Declaration (HPD)   100 Ppm Disclosure
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	
MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

Installation Guidelines

Maintenance Guidelines









Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Cinnamon 06001 LRV 14.9   L* 45.47 V3 - Moderate Variation	Tannery Brown 06002 LRV 10.3   L* 38.4 V2 - Slight Variation	Summer Truffle 06003 LRV 9.2   L* 36.34 V2 - Slight Variation	Abyss 06004 LRV 6.6   L* 30.97 V3 - Moderate Variation	Ivory 06005 LRV 25.4   L* 57.48 V2 - Slight Variation	Bone 06006 LRV 23   L* 55.05 V4 - Substantial Variation
					
Morchella 06007 LRV 9.5   L* 36.84 V2 - Slight Variation	Cremini 06008 LRV 35.6   L* 66.23 V3 - Moderate Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

