

Stratum Eiris


系列	Stratum	
款型编号	053UV	
结构	附软木垫层的多层WPC	
类型	Class III, Type B	
附加垫层	软木	
表面处理	ExoGuard®	
	美国	尺寸标准
公称尺寸	7 in w x 59 in l	18 cm w x 150 cm l
实际尺寸	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
耐磨层厚度	30 mil (0.03 in)	0.76 mm
产品整体厚度	0.335 in	8.5 mm
边缘轮廓	微斜角	
Installation Type	Click	
安装方式	Floating Or Direct Glue	
胶粘剂建议	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or Shaw 4100	

包装

每盒件数	6 pcs	
每箱面积	17.43 sq ft	1.62 sq m
每箱重量	33.95 lbs	15.4 kg



铺装建议



搭配产品

COREtec: Stratum 500, Stratum 700, Stratum XI, Defined, Stratum Nordic

性能 + 测试

残余压痕 (ASTM F1914)	Passes
耐热性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐化学性 (ASTM F925)	Passes
辐射板 (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

质保

15年商用有限质保

属性+认证

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 认证
Greenguard Gold | 认证

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

通过ISO 14025、EN 15804和ISO 21930 : 2017等第三方认证
11.5 Kg CO₂/M²
41% (Pre-Consumer 41% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | 中国

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
- X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
- Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
- X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
Greenguard Gold Certificate

绿色leed贡献信用

- MR Credit : 建立产品披露与优化
材料成分-选项1 : 材料成分报告
- MR Credit : 建立产品披露和优化
环境产品声明-选项1 : 环境产品声明 (EPD)
- EQ信用 : 低排放材料
选项1 : 产品类别计算
- Installation Guidelines
- Maintenance Guidelines

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore & Greenguard Gold Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Cinnamon 06001
LRV 14.9 | L* 45.47
V3 - Moderate Variation



Tannery Brown 06002
LRV 10.3 | L* 38.4
V2 - Slight Variation



Summer Truffle 06003
LRV 9.2 | L* 36.34
V2 - Slight Variation



Abyss 06004
LRV 6.6 | L* 30.97
V3 - Moderate Variation



Ivory 06005
LRV 25.4 | L* 57.48
V2 - Slight Variation



Bone 06006
LRV 23 | L* 55.05
V4 - Substantial Variation



Morchella 06007
LRV 9.5 | L* 36.84
V2 - Slight Variation



Cremini 06008
LRV 35.6 | L* 66.23
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

