

## Stratum Eiris


Collection	<b>Stratum</b>	
Numéro De Style	<b>053UV</b>	
Construction	<b>WPC Multicouche Avec Sous-Couche EN Liège Attachée</b>	
classe	<b>Class III, Type B</b>	
Endos Intégrée	<b>Liège</b>	
Finition	<b>ExoGuard®</b>	
	Impérial	Métrique
Dimensions Nominales	<b>7 in w x 59 in l</b>	<b>18 cm w x 150 cm l</b>
Dimensions Réelles	<b>7.09 in w x 59.06 in l</b>	<b>18.01 cm w x 150.01 cm l</b>
Épaisseur De La Couche d'Usure	<b>30 mil (0.03 in)</b>	<b>0.76 mm</b>
Épaisseur Générale Du Produit	<b>0.335 in</b>	<b>8.5 mm</b>
Profil Du Bord	<b>Micro-Biseau</b>	
Installation Type	<b>Click</b>	
Installation	<b>Floating Or Direct Glue</b>	
Adhésif Recommandé	<b>4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or Shaw 4100</b>	



### Emballage

Pièces Par Carton	<b>6 pcs</b>	
Surface Par Carton	<b>17.43 sq ft</b>	<b>1.62 sq m</b>
Poids Par Carton	<b>33.95 lbs</b>	<b>15.4 kg</b>

### Méthodes d'Installation Conseillées



### Coordination Des Produits

None: Stratum 1200  
COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined

### Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	<b>Passes</b>
Résistance À La Chaleur (Astm F1514)	<b>Passes</b>
Résistance À La Lumière (Astm F1515)	<b>Passes</b>
Résistance Chimique (Astm F925)	<b>Passes</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Total Recycled Content	41% (Pre-Consumer 41%   Post-Consumer 0%)
Global Product Assessment	
	FloorScore®   Agréé
	Greenguard (Certification, Gold, Private Label)   Agréé
	Country of Origin   Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgateion et optimisation des produits de construction	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b> <b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b> <b>FloorScore &amp; Greenguard Gold Certified</b>
« Crédit MR : Divulgateion et optimisation des produits de construction	
Crédit EQ : matériaux faibles émissions	

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways

					
Cinnamon 06001 LRV 14.9 V3 - Moderate Variation	Tannery Brown 06002 LRV 10.3 V2 - Slight Variation	Summer Truffle 06003 LRV 9.2 V2 - Slight Variation	Abyss 06004 LRV 6.6 V3 - Moderate Variation	Ivory 06005 LRV 25.4 V2 - Slight Variation	Bone 06006 LRV 23 V4 - Substantial Variation




### Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1


Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation

