

Stratum Eiris


コレクション	Stratum	
スタイルナンバー	053UV	
建設	コルク下敷を含む多層WPC	
クラス	Class III, Type B	
付属下敷	コルク	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	7 in w x 59 in l	18 cm w x 150 cm l
実際の寸法	7.09 in w x 59.06 in l	18.01 cm w x 150.01 cm l
摩耗層の厚さ	30 mil (0.03 in)	0.76 mm
製品全体の厚さ	0.335 in	8.5 mm
エッジプロファイル	マイクロベベル	
Installation Type	Click	
インストール	Floating Or Direct Glue	
推奨接着剤	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or Shaw 4100	

包装

ボックスあたりの個数	6 pcs	
ボックスあたりの面積	17.43 sq ft	1.62 sq m
ボックスあたりの重量	33.95 lbs	15.4 kg



推奨インストール方法



コーディネート商品

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Linear, Defined, Stratum Nordic

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Total Recycled Content	41% (Pre-Consumer 41% Post-Consumer 0%)
Global Product Assessment	
	FloorScore® 認証取得
	Greenguard (Certification, Gold, Private Label) 認証取得
	Country of Origin 中国

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 材料成分-オプション1：材料成分レポート	Health Product Declaration (HPD) 100 Ppm Disclosure
MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore & Greenguard Gold Certified
Installation Guidelines	
Maintenance Guidelines	

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cinnamon 06001 LRV 14.9 V3 - Moderate Variation	Tannery Brown 06002 LRV 10.3 V2 - Slight Variation	Summer Truffle 06003 LRV 9.2 V2 - Slight Variation	Abyss 06004 LRV 6.6 V3 - Moderate Variation	Ivory 06005 LRV 25.4 V2 - Slight Variation	Bone 06006 LRV 23 V4 - Substantial Variation
					
Morchella 06007 LRV 9.5 V2 - Slight Variation	Cremini 06008 LRV 35.6 V3 - Moderate Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

