

Stratum Linear

Collection	Stratum	
Numéro De Style	055UV	
Construction	WPC Multicouche Avec Sous-Couche EN Liège Attachée	
classe	Class III, Type B	
Endos Intégrée	Liège	
Finition	ExoGuard®	
Dimensions Nominales	Impérial	Métrique
	9 in w x 24 in l	23 cm w x 61 cm l
	8.98 in w x 24.02 in l	22.81 cm w x 61.01 cm l
	30 mil (0.03 in)	0.76 mm
	0.323 in	8.2 mm
	Bevel	
	Click	
Dimensions Réelles	Floating Or Direct Glue	
Épaisseur De La Couche d'Usure	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1	
Épaisseur Générale Du Produit	Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	
Profil Du Bord		
Installation Type		
Installation		
Adhésif Recommandé		

Emballage

Pièces Par Carton	16 pcs	
Surface Par Carton	23.95 sq ft	2.23 sq m
Poids Par Carton	46.3 lbs	21 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

None: Stratum 1200
COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Eiris, Defined

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Essai Au Panneau Radiant (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Agréé

Climate Impact

- Environmental Product Declaration (EPD)
- Total Recycled Content

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
41% (Pre-Consumer 41% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

Contribution Au Certificat Vert Leed

- « Crédit MR : Divulgence et optimisation des produits de construction
- « Crédit MR : Divulgence et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)
[Maintenance Guidelines](#)


Health Product Declaration (HPD) | 100 Ppm Disclosure
3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.


Available Colorways




True Black 04001
V2 - Slight Variation



Dulled Flint 04002
V2 - Slight Variation



Ripe Olive 04004
V2 - Slight Variation




Dusty Suede 04005
V2 - Slight Variation

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2




Slight Variation

V3



Moderate Variation

V4



Substantial Variation

