

Stratum Linear


Coleção	Stratum	
Número Do Produto	055UV	
Construção	WPC Multicamada Com Camada De Cortiça Anexada	
classe	Class III, Type B	
Manta Inferior Adicional	Cortiça	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	9 in w x 24 in l	23 cm w x 61 cm l
Dimensões Reais	8.98 in w x 24.02 in l	22.81 cm w x 61.01 cm l
Espessura Da Camada De Uso	30 mil (0.03 in)	0.76 mm
Espessura Total Do Produto	0.323 in	8.2 mm
Perfil De Borda	Chanfrado	
Installation Type	Click	
Instalação	Floating Or Direct Glue	
Adesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	



Empacotamento

Peças Por Caixa	16 pcs	
Área Por Caixa	23.95 sq ft	2.23 sq m
Peso Por Caixa	46.3 lbs	21 kg

Método De Instalação Recomendado



Produtos Coordenados

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Eiris, Defined

desempenho + teste

recuo residual (ASTM F1914)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
painel radiante (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.2 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	41% (Pre-Consumer 41%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>Greenguard Gold Certificate</b>

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	<b>FloorScore® Certified</b>

[Installation Guidelines](#)


[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways




True Black 04001  
V2 - Slight Variation



Dulled Flint 04002  
V2 - Slight Variation



Ripe Olive 04004  
V2 - Slight Variation



Dusty Suede 04005  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

