

Defined


Colección	Stratum	
Número De Estilo	058UV	
Construcción	WPC Multicapa Con Base De Corcho Adjunta	
clase	Class III, Type B	
Manta Inferior Adicional	Corcho	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	7.09 in w x 48.03 in l	18.01 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.315 in	8 mm
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	



Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	23.64 sq ft	2.2 sq m
Peso Por Caja	39.68 lbs	18 kg

Método De Instalación Recomendado



Productos Que Combinan

None: Stratum 1200
COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Eiris, Stratum Linear

Desempeño + Pruebas

Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017

Total Recycled Content

41% (Pre-Consumer 41% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado

Greenguard (Certification, Gold, Private Label) | Certificado

Country of Origin | China

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales

Health Product Declaration (HPD) | 100 Ppm Disclosure

Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto

FloorScore & Greenguard Gold Certified

[Installation Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

[Maintenance Guidelines](#)

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.


Available Colorways



Specify 03001
V4 - Substantial Variation



Express 03002
V3 - Moderate Variation



Exemplify 03004
V3 - Moderate Variation




Detail 03005
V3 - Moderate Variation



Elucidate 03006
V4 - Substantial Variation



Represent 03007
V4 - Substantial Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

