

Artesian Sheet


| | | |
|---------------------------|---|---------|
| Collection | Quite Canvas | |
| Style Number | 0718V | |
| class | Type I, Grade 1, Class C | |
| Backing Class | Closed Cell Foam | |
| Finish | UV Urethane | |
| | U.s. | Metric |
| Wear Layer Thickness | 10 mil (0.01 in) | 0.25 mm |
| Overall Product Thickness | 0.08 in | 2 mm |
| Recommended Adhesive | S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|--------------------------|----------------------|
| Actual Roll Size | 12.00 ft w x 108.00 ft l | 3.66 m w x 32.92 m l |
| Area Per Roll | 144 sy/roll | 120.4 sq m/roll |
| Weight Per Roll | 381.6 lbs | 173.09 kg |



Recommended Installation Method



Performance + Testing

| | | |
|--|---|---|
| Static Load (Astm F970) | Passes (Modified), *1500 lbs | This Test Is Intended To Compare Relative Properties Of Different Styles And Constructions. Results Are Based On A Laboratory Test And Used For Comparative Purposes - Real Life Load Limit May Vary. |
| Residual Indentation (Astm F1914) | Passes | |
| Flexibility (Astm F137) | Passes | |
| Resistance To Heat (Astm F1514) | Passes | |
| Resistance To Light (Astm F1515) | Passes | |
| Resistance To Chemicals (Astm F925) | Passes | |
| Radiant Panel (Astm E648) | Passes, Class I | |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | | |

Warranties

5 Year Commercial Limited
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure FloorScore® Certified |
| Indoor Air Quality | |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 7.04 Kg CO ₂ /M ² 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Embodied Carbon (Cradle to Gate) | |
| Total Recycled Content | |
| Global Product Assessment | Country of Origin Imported |

Leed Contribution Credit

| | |
|---|--|
| MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting | Health Product Declaration (HPD) 100 Ppm Disclosure |
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials Option 1: Product Category Calculations | FloorScore Certified |

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Stonework 00112
V2 - Slight Variation



Corinth 00141
V3 - Moderate Variation



Woodhaven 00192
V3 - Moderate Variation



Historian 00201
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

