

Artesian Sheet


| | | |
|--------------------------------|--|----------|
| Collection | Quite Canvas | |
| Numéro De Style | 0718V | |
| Construction | Feuille Hétérogène Commerciale Légère Avec Fibre De Verre | |
| classe | Type I, Grade 1, Class C | |
| Classe d'Endos | Mousse à cellules fermées | |
| Finition | UV Urethane | |
| Épaisseur De La Couche d'Usure | Impérial | Métrique |
| | 10 mil (0.01 in) | 0.25 mm |
| Épaisseur Générale Du Produit | 0.08 in | 2 mm |
| Adhésif Recommandé | S150-95 Resilient Sheet Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient Sheet or 4151 Multi-Use Premium | |

Emballage

| | | |
|-------------------------------|--------------------------|----------------------|
| Dimensions Réelles Du Rouleau | 12.00 ft w x 108.00 ft l | 3.66 m w x 32.92 m l |
| Surface Par Rouleau | 144 sy/roll | 120.4 sq m/roll |
| Poids Par Rouleau | 381.6 lbs | 173.09 kg |



Méthodes d'Installation Conseillées



performance + Tests et essai

| | | |
|--|------------------------------|--|
| charge statique (ASTM F970) | Passes (Modified), *1500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| poinçonnement rémanent (ASTM F1914) | Passes | |
| Flexibility (ASTM F137) | Passes | |
| résistance à la chaleur (ASTM F1514) | Passes | |
| résistance à la lumière (ASTM F1515) | Passes | |
| résistance chimique (ASTM F925) | Passes | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |
| Essai au panneau radiant (Astm E648) | Passes, Class I | |
| coefficient de frottement (ASTM D2407, résistance au glissement) | | |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

- Commercial 15 Year Underbed Bond Warranty
- 5 Year Light Commercial Limited Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributs + Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Agréé |
| Climate Impact | |
| Environmental Product Declaration (EPD) | Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 7.04 Kg Co ₂ /M ² |
| Life-Cycle Carbon Emissions | Low Embodied Carbon |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|---|---|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt | Absence of Heavy Metals |
| X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt | Absence of Halogenated Flame Retardants |
| Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt | Ortho-Phthalates |
| X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt | FloorScore Certificate |

Contribution Au Certificat Vert Leed

| | |
|---|---|
| « Crédit MR : Divulgateion et optimisation des produits de construction | Health Product Declaration (HPD) 100 Ppm Disclosure |
| « Crédit MR : Divulgateion et optimisation des produits de construction | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Crédit EQ : matériaux faibles émissions | FloorScore Certified |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. Visit shawcontract.com/testing for more information. |
| Maintenance Guidelines | |
| | |

Available Colorways



Stonework 00112
V2 - Slight Variation



Corinth 00141
V3 - Moderate Variation



Woodhaven 00192
V3 - Moderate Variation



Historian 00201
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

