

Artesian Sheet

コレクション	Quite Canvas	
スタイルナンバー	0718V	
建設	グラスファイバー入り軽量商用異質シート	
クラス	Type I, Grade 1, Class C	
バックイングクラス	クローズド セル フォーム	
仕上げ	UV Urethane	
摩耗層の厚さ	米国	メートル法
製品全体の厚さ	10 mil (0.01 in)	0.25 mm
推奨接着剤	0.08 in	2 mm
	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
ロールあたりの面積	144 sq ft/roll	120.4 sq m/roll
ロールごとの重量	381.6 lbs	173.09 kg



推奨インストール方法



Straight

パフォーマンス + テスト

静荷重 (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
残留圧痕 (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
耐熱性 (ASTM F1514)	Passes	
耐光性 (ASTM F1515)	Passes	
耐薬品性 (ASTM F925)	Passes	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes
放射パネル (ASTM E648)	Passes, Class I	
摩擦係数 (ASTM D2407、滑り抵抗)		

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

[Commercial 15 Year Underbed Bond Warranty](#)
[5 Year Light Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

属性+認定

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 認証取得

Climate Impact

Environmental Product Declaration (EPD)

ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得

Embodied Carbon (Cradle to Gate)

7.04 Kg CO₂/M²

Life-Cycle Carbon Emissions

Low Embodied Carbon

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

Absence of Asbestos

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt

Absence of Heavy Metals

X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt

Absence of Halogenated Flame Retardants

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt

Ortho-Phthalates

X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

FloorScore Certificate

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築
材料成分-オプション1：材料成分レポート

Health Product Declaration (HPD) | 100 Ppm Disclosure

MRクレジット：製品の開示と最適化の構築
環境製品宣言-オプション1：環境製品宣言 (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

EQクレジット：低排出材料
オプション1：製品カテゴリの計算

FloorScore® Certified

[Installation Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.

[Maintenance Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Stonework 00112
V2 - Slight Variation



Corinth 00141
V3 - Moderate Variation



Woodhaven 00192
V3 - Moderate Variation



Historian 00201
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

