

Artesian Sheet


コレクション	Quite Canvas	
スタイルナンバー	0718V	
建設	グラスファイバー入り軽量商用異質シート	
クラス	Type I, Grade 1, Class C	
バックイングクラス	クローズド セル フォーム	
仕上げ	UV Urethane	
摩耗層の厚さ 製品全体の厚さ 推奨接着剤	米国	メートル法
	10 mil (0.01 in)	0.25 mm
	0.08 in	2 mm
	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
ロールあたりの面積	144 sy/roll	120.4 sq m/roll
ロールごとの重量	381.6 lbs	173.09 kg



推奨インストール方法



Straight

パフォーマンス + テスト

静荷重 (astm F970)	Passes (Modified), *1500 lbs
残留圧痕 (astm F1914)	Passes
柔軟性 (astm F137)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
放射パネル (astm E648)	Passes, Class I
摩擦係数(astm D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

このテストは、さまざまなスタイルと構造の相対的な特性を比較することを目的としています。結果は実験室でのテストに基づいており、比較の目的で使用されています。実際の負荷制限は異なる場合があります。

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

5年間の商用限定保証  
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

属性+認定

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | 認証取得

Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得  
7.04 Kg CO<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築  
材料成分-オプション1：材料成分レポート  
MRクレジット：製品の開示と最適化の構築  
環境製品宣言-オプション1：環境製品宣言 (EPD)  
EQクレジット：低排出材料  
オプション1：製品カテゴリの計算

Health Product Declaration (HPD) | 100 Ppm Disclosure  
  
3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
FloorScore Certified

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.  
  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Stonework 00112  
V2 - Slight Variation



Corinth 00141  
V3 - Moderate Variation



Woodhaven 00192  
V3 - Moderate Variation



Historian 00201  
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

