

Artesian Sheet

수집	Quite Canvas	
스타일 번호	0718V	
수업	Type I, Grade 1, Class C	
후원 수업	페쇄세포 폼	
끝	UV Urethane	
	미국	미터법
마모 층 두께	10 mil (0.01 in)	0.25 mm
전체 제품 두께	0.08 in	2 mm
권장 접착제	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

포장

실제 롤 크기	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
롤당 면적	144 sy/roll	120.4 sq m/roll
롤 당 무게	381.6 lbs	173.09 kg



권장 설치 방법



Straight

공연 + 테스트

정적 하중 (Astm F970)
잔차 들어 쓰기 (Astm F1914)
유연성 (Astm F137)
내열성 (Astm F1514)
내광성 (Astm F1515)
화학 물질에 대한 내성 (Astm F925)
복사 패닐 (Astm E648)
마찰 계수(astm D2407, 미끄러짐 저항)

Passes (Modified), *1500 lbs
Passes
Passes
Passes
Passes
Passes
Passes, Class I
>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

이 테스트는 다양한 스타일과 구성의 상대적인 속성을 비교하기위한 것입니다. 결과는 실험실 테스트를 기반으로하며 비교 목적으로 사용됩니다. 실제 하중 한계는 다를 수 있습니다.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

5년 상용 제한

[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 인증

Climate Impact

Environmental Product Declaration (EPD)
Embodied Carbon (Cradle to Gate)
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득
7.04 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축
재료 성분-옵션 1 : 재료 성분보고
MR 크레딧 : 제품 공개 및 최적화 구축
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)
EQ 크레딧 : 저 발광 재료
옵션 1 : 제품 범주 계산

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Installation Guidelines
Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Stonework 00112
V2 - Slight Variation



Corinth 00141
V3 - Moderate Variation



Woodhaven 00192
V3 - Moderate Variation



Historian 00201
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



