

Artesian Sheet


Coleção	Quite Canvas	
Número Do Produto	0718V	
Construção	Manta Heterogênea De Uso Comercial, Tráfego Leve, Com Fibra De Vidro	
classe	Type I, Grade 1, Class C	
Tipo De Base	Espuma de Célula Fechada	
Acabamento	UV Urethane	
	U.s.	Metric
Espessura Da Camada De Uso	10 mil (0.01 in)	0.25 mm
Espessura Total Do Produto	0.08 in	2 mm
Adesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Tamanho Real Do Rolo	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
Área Por Rolo	144 sy/roll	120.4 sq m/roll
Peso Por Rolo	381.6 lbs	173.09 kg



Método De Instalação Recomendado



desempenho + teste

carga estática (ASTM F970)
recuo residual (ASTM F1914)
Flexibility (ASTM F137)
resistência ao calor (ASTM F1514)
resistência à luz (ASTM F1515)
resistência a produtos químicos (ASTM F925)
painel radiante (ASTM E648)
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)

Passes (Modified), *1500 lbs
Passes
Passes
Passes
Passes
Passes, Class I
>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

\*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

- Commercial 15 Year Underbed Bond Warranty
- 5 Year Light Commercial Limited Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	7.04 Kg Co <sub>2</sub> /M <sup>2</sup>
Life-Cycle Carbon Emissions	Low Embodied Carbon
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	<b>FloorScore® Certified</b>

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Stonework 00112  
V2 - Slight Variation



Corinth 00141  
V3 - Moderate Variation



Woodhaven 00192  
V3 - Moderate Variation



Historian 00201  
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

