

Artesian Sheet


Collection	Quite Canvas	
Numéro Du Style	0718V	
Construction	Lame De Vinyle De Luxe Commercial Légère	
Classement	Type I, Grade 1, Class C	
Classement De La Sous-couche	Mousse à cellules fermées	
Finition	UV Urethane	
	U.s.	Metric
Épaisseur De La Couche d'Usure	10 mil (0.01 in)	0.25 mm
Épaisseur Générale Du Produit	0.08 in	2 mm
Adhésif Recommandé	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Packaging

Dimensions Réelles Du Rouleau	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
Surface Par Rouleau	144 sy/roll	120.4 sq m/roll
Poids Par Rouleau	381.6 lbs	173.09 kg



Méthodes d'Installation Conseillées



Performance + Tests Et Essai

Empreinte Résiduelle (Astm F1914)	Passes
Souplesse (Astm F137)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 5 Ans](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Transparence du produit

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Heterogeneous Sheet products are UL Certified with an Industry-Wide EPD and are assessed for impacts on human health and the environment.

Attributs + Certifications

Déclaration sanitaire de produit (HPD)	<a href="#">1000 ppm Disclosure</a>
Déclaration environnementale de produit (EPD)	<a href="#">Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14025, EN15804 &amp; ISO 21930:2017</a>
Embodied Carbon (Cradle to Gate)	7.04 Kg Co <sub>2</sub> /M <sup>2</sup>
FloorScore®	<a href="#">Certifié</a>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
pays d'origine	Canada

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD)   100 Ppm Disclosure
MR Credit: Building Product Disclosure and Optimisation Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
"Crédit EQ : matériaux faibles émissions Option 1 : calculs par catégorie de produit"	FloorScore Certified

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Stonework 00112  
V2 - Slight Variation



Corinth 00141  
V3 - Moderate Variation



Woodhaven 00192  
V3 - Moderate Variation



Historian 00201  
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

