

Artesian Sheet

Collectie	Quite Canvas	
Stijlnummer	0718V	
Uitzicht	Licht Commercieel Heterogeen Blad Met Glasvezel	
klasse	Type I, Grade 1, Class C	
Klasse Van De Backing	Gesloten Celschuim	
Afwerking	UV Urethane	
	U.s.	Metric
Dikte Slijtlaag	10 mil (0.01 in)	0.25 mm
Totale Dikte Van Het Product	0.08 in	2 mm
Aanbevolen Kleefstof	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Verpakking

Werkelijke Rolgrootte	12.00 ft w x 108.00 ft l	3.66 m w x 32.92 m l
Oppervlakte Per Rol	144 sy/roll	120.4 sq m/roll
Gewicht Per Rol	381.6 lbs	173.09 kg



Aanbevolen Installatiemethode



Straight

Prestatie + Testen

Resterende Indeuking (Astm F1914)	Passes
Flexibiliteit (Astm F137)	Passes
Hittebestendigheid (Astm F1514)	Passes
Weerstand Tegen Licht (Astm F1515)	Passes
Weerstand Tegen Chemicaliën (Astm F925)	Passes
Wrijvingscoëfficiënt (Astm D2407, Slipweerstand)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[5 Jaar Beperkt Commercieel](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

## producttransparantie

Shaw Contract streeft ernaar klanten een bouwchemie te bieden die veilig en betrouwbaar is. Samen zullen wij u helpen uw doelstellingen op het gebied van materiaalgezondheid te bereiken. Heterogene

## Kenmerken + Certificeringen

Health Product Declaration (HPD)

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

FloorScore®

Total Recycled Content

land van herkomst

[1000 ppm Disclosure](#)[3de Partij Gecertificeerd in Overeenstemming Met ISO 14025, EN 15804, & ISO 21930:2017](#)**7.04 Kg Co<sub>2</sub>/M<sup>2</sup>**[Gecertificeerd](#)**0% (Pre-Consumer 0% | Post-Consumer 0%)****Canada**

## WELL V2 Contribution Credit

X01 Fundamental Material Precautions  
Part 1: (C): Restrict Asbestos PreconditionX08 Hazardous Material Reduction  
Part 1: Limit Hazardous Materials OptimizationX10 Volatile Compound Reduction  
Part 1 (A): Manage Volatile Organic Compounds (VOCs) OptimizationX10 Volatile Compound Reduction  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) OptimizationX11 Long Term Emissions Control  
Part 2: Flooring Optimization**Absence of Asbestos****Absence of Heavy Metals****Absence of Halogenated Flame Retardants****Ortho-Phthalates****FloorScore Certificate**

## Groen Leed Bijdragekrediet

"MR-krediet: Openbaarmaking en optimalisering van bouwproducten  
Materiaal ingrediënten - Optie 1: Rapportage materiaal ingrediënten""MR-krediet: openbaarmaking en optimalisering van bouwproducten  
Milieuproductverklaringen - Optie 1: Milieuproductverklaring (EPD)"

"EQ-krediet: materialen met lage emissie Optie 1: Berekeningen per productcategorie"

**Health Product Declaration (HPD) | 100 Ppm Disclosure****3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017****FloorScore Certified**[Installation Guidelines](#)[Maintenance Guidelines](#)Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Stonework 00112  
V2 - Slight Variation



Corinth 00141  
V3 - Moderate Variation



Woodhaven 00192  
V3 - Moderate Variation



Historian 00201  
V4 - Substantial Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

