

Rethink

| | | |
|----------------------|--|-------------------------|
| Collection | Rethink | |
| Style Number | 0733V | |
| Construction | Commercial Woven Luxury Vinyl Tile | |
| Class / ASTM F1700 | Class II, Type B | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Nominal Dimensions | 9 in w x 36 in l | 23 cm w x 91 cm l |
| Actual Dimensions | 9.00 in w x 36.00 in l | 22.86 cm w x 91.44 cm l |
| Overall Thickness | 0.118 in | 3 mm |
| Edge Profile | Squared Edge | |
| Installation Type | Dry Back | |
| Installation | Direct Glue | |
| Recommended Adhesive | S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|-------------------|-----------|-----------|
| Pieces Per Carton | 16 pcs | |
| Area Per Carton | 36 sq ft | 3.34 sq m |
| Weight Per Carton | 37.48 lbs | 17 kg |



Recommended Installation Method



Performance + Testing

| | |
|---|---|
| Resistance To Heat (Astm F1514) | Passes |
| Resistance To Light (Astm F1515) | Passes |
| Resistance To Chemicals (Astm F925) | Passes |
| Radiant Panel (Astm E648) | Passes, Class I |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 7.31 Kg CO ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | |
| | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

Green Leed Contribution Credit

| | |
|---|--|
| MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting | Health Product Declaration (HPD) 100 Ppm Disclosure |
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials Option 1: Product Category Calculations | FloorScore Certified |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information. |
| Maintenance Guidelines | |

Available Colorways

| | | | | | |
|--|--|---|---|---|---|
|  <div>Hybrid 33100 LRV 20.4 L* 52.26 V1 - Uniform Appearance</div> |  <div>Structure 33150 LRV 18.9 L* 50.53 V1 - Uniform Appearance</div> |  <div>Minimal 33155 LRV 30.7 L* 63.58 V1 - Uniform Appearance</div> |  <div>Essence 33340 LRV 22.7 L* 54.76 V1 - Uniform Appearance</div> |  <div>Energy 33405 LRV 16.4 L* 47.53 V1 - Uniform Appearance</div> |  <div>Carbon 33505 LRV 12.2 L* 41.52 V1 - Uniform Appearance</div> |
|  <div>Core 33515 LRV 32.7 L* 63.93 V1 - Uniform Appearance</div> |  <div>Metal 33530 LRV 20.7 L* 52.62 V1 - Uniform Appearance</div> |  <div>Industry 33751 LRV 14.9 L* 45.47 V1 - Uniform Appearance</div> |  <div>Element 33755 LRV 16.5 L* 47.66 V1 - Uniform Appearance</div> |  <div>Smart 33856 LRV 17.3 L* 48.58 V1 - Uniform Appearance</div> |  <div>Innovate 33991 LRV 17.1 L* 48.38 V1 - Uniform Appearance</div> |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

