

Tatami Sheet


| | | |
|---------------------------|---|---------|
| Collection | Terasu | |
| Style Number | 0796V | |
| Welding Rod Style Number | 353VS | |
| Construction | Commercial Heterogeneous Sheet With Fiberglass | |
| class | Type I, Grade 1, Class B | |
| Backing Class | 4-ply fused backing system | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Product Thickness | 0.087 in | 2.2 mm |
| Installation Type | Dry Back | |
| Recommended Adhesive | S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.56 ft w x 68.58 ft l | 2.00 m w x 20.90 m l |
| Area Per Roll | 50.75 sy/roll | 42.43 sq m/roll |
| Weight Per Roll | 337.7 lbs | 153.18 kg |



Recommended Installation Method



Coordinating Products

Sheet: Reed Sheet, Roji Sheet
Carpet Tile: Botan Tile, Hana Tile, Kusa Tile
Broadloom: Botan, Hana, Kusa

performance + testing

| | |
|---|---|
| residual indentation (ASTM F1914) | Passes |
| Flexibility (ASTM F137) | Passes |
| resistance to heat (ASTM F1514) | Passes |
| resistance to light (ASTM F1515) | Passes |
| resistance to chemicals (ASTM F925) | Passes |
| radiant panel (ASTM E648) | Passes, Class I |
| coefficient of friction (ASTM D2407, slip resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 9.4 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

Leed Contribution Credit

| | |
|--|---|
| MR Credit: Building Product Disclosure and Optimization | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | FloorScore® Certified |
| EQ Credit: Low Emitting Materials | |
| Option 1: Product Category Calculations | |

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|--|--|
|  <div>Pebble 96114 Weldrod 07332</div> |  <div>Evening Glow 96130 Weldrod 07331</div> |  <div>Tea Garden 96216 Weldrod 07332</div> |  <div>Moss 96330 Weldrod 07332</div> |  <div>Cascade 96416 Weldrod 05008</div> |  <div>Tidal Basin 96440 Weldrod 02003</div> |
|  <div>Zen 96515 Weldrod 01203</div> |  <div>Wind Chime 96530 Weldrod 01225</div> |  <div>Stroll 96535 Weldrod 01203</div> |  <div>Stepping Stone 96700 Weldrod 02001</div> |  <div>Pagoda 96710 Weldrod 05244</div> |  <div>Shakkei 96761 Weldrod 02001</div> |

