

Tatami Sheet

コレクション	Terasu	
スタイルナンバー	0796V	
溶接棒スタイル番号	353VS	
建設	グラスファイバー入りの商業用異種シート	
クラス	Type I, Grade 1, Class B	
バックングクラス	4層溶融バックングシステム	
仕上げ	ExoGuard®	
	米国	メートル法
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.087 in	2.2 mm
Installation Type	Dry Back	
推奨接着剤	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
ロールあたりの面積	50.75 sy/roll	42.43 sq m/roll
ロールごとの重量	337.7 lbs	153.18 kg



推奨インストール方法



Reverse

コーディネート商品

Sheet: Reed Sheet, Roji Sheet
Carpet Tile: Botan Tile, Hana Tile, Kusa Tile
Broadloom: Botan, Hana, Kusa

パフォーマンス + テスト

残留圧痕 (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
耐熱性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐薬品性 (ASTM F925)	Passes
放射パネル (ASTM E648)	Passes, Class I
摩擦係数(ASTM D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

属性+認定

Health & Wellbeing	
Indoor Air Quality	FloorScore® 認証取得
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 第三者認証取得 Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言（EPD）	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore® Certified

Installation Guidelines
Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Pebble 96114 Weldrod 07332	Evening Glow 96130 Weldrod 07331	Tea Garden 96216 Weldrod 07332	Moss 96330 Weldrod 07332	Cascade 96416 Weldrod 05008	Tidal Basin 96440 Weldrod 02003
					
Zen 96515 Weldrod 01203	Wind Chime 96530 Weldrod 01225	Stroll 96535 Weldrod 01203	Stepping Stone 96700 Weldrod 02001	Pagoda 96710 Weldrod 05244	Shakkei 96761 Weldrod 02001

