

Tatami Sheet

コレクション	Terasu	
スタイルナンバー	0796V	
溶接棒スタイル番号	353VS	
建設	グラスファイバー入りの商業用異種シート	
クラス	Type I, Grade 1, Class B	
バックングクラス	4層溶融バックングシステム	
仕上げ	ExoGuard®	
	米国	メートル法
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.087 in	2.2 mm
Installation Type	Dry Back	
推奨接着剤	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

実際のロールサイズ	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
ロールあたりの面積	50.75 sy/roll	42.43 sq m/roll
ロールごとの重量	337.7 lbs	153.18 kg



推奨インストール方法



コーディネート商品

Sheet: Reed Sheet, Roji Sheet
Carpet Tile: Botan Tile, Hana Tile, Kusa Tile
Broadloom: Botan, Hana, Kusa

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
柔軟性 (astm F137)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
放射パネル (astm E648)	Passes, Class I
摩擦係数(astm D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Health & Wellbeing	
Indoor Air Quality	FloorScore® 認証取得
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 第三者認証取得 Country of Origin Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築
環境製品宣言-オプション1：環境製品宣言 (EPD)
EQクレジット：低排出材料
オプション1：製品カテゴリーの計算

[Installation Guidelines](#)
[Maintenance Guidelines](#)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
Visit shawcontract.com/testing for more information.

Available Colorways

					
Pebble 96114 Weldrod 07332	Evening Glow 96130 Weldrod 07331	Tea Garden 96216 Weldrod 07332	Moss 96330 Weldrod 07332	Cascade 96416 Weldrod 05008	Tidal Basin 96440 Weldrod 02003
					
Zen 96515 Weldrod 01203	Wind Chime 96530 Weldrod 01225	Stroll 96535 Weldrod 01203	Stepping Stone 96700 Weldrod 02019	Pagoda 96710 Weldrod 05244	Shakkei 96761 Weldrod 02001