

## Roji Sheet


|                          |  |                |
|--------------------------|--|----------------|
| Collection               | <b>Terasu</b>  |                |
| Style Number             | <b>0798V</b>   |                |
| Welding Rod Style Number | <b>353VS</b>   |                |
| Construction             | <b>Commercial Heterogeneous Sheet With Fiberglass</b>  |                |
| Class / ASTM F1303       | <b>Type I, Grade 1, Class B</b>  |                |
| Backing Class            | <b>4-ply Fused Backing System</b>  |                |
| Finish                   | <b>ExoGuard®</b>   |                |
|                          | U.S.   | Metric         |
| Wear Layer Thickness     | <b>20 mil (0.02 in)</b>  | <b>0.51 mm</b> |
| Overall Thickness        | <b>0.087 in</b>  | <b>2.2 mm</b>  |
| Recommended Adhesive     | <b>S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon</b> |                |

### Packaging

|                  |                               |                             |
|------------------|-------------------------------|-----------------------------|
| Actual Roll Size | <b>6.56 ft w x 68.58 ft l</b> | <b>2.00 m w x 20.90 m l</b> |
| Area per Roll    | <b>50.75 sy/roll</b>          | <b>42.43 sq m/roll</b>      |
| Weight per Roll  | <b>337.7 lbs</b>              | <b>153.18 kg</b>            |



### Recommended Installation Method



### Coordinating Products

- Sheet: Tatami Sheet, Reed Sheet
- LVT: Terrace 2.5 Mm, Terrace 5.0 Mm
- Carpet Tile: Botan Tile, Hana Tile, Kusa Tile
- Broadloom: Botan, Hana, Kusa

Performance + Testing

|  |   |  |  |
|--|---|--|--|
| Static Load (ASTM F970)  | Passes (Modified), *2000 lbs  | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |  |
| Residual Indentation (ASTM F1914)  | Passes  |  |  |
| Flexibility (ASTM F137)  | Passes  |  |  |
| Resistance to Heat (ASTM F1514)  | Passes  |  |  |
| Resistance to Light (ASTM F1515)   | Passes  |  |  |
| Resistance to Chemicals (ASTM F925)  | Passes  |  |  |
| Radiant Panel (ASTM E648)  | Passes, Class I   |  |  |
| Coefficient of Friction (ASTM D2047, Slip Resistance)  | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |  |  |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. |   |  |  |

Warranties

- 15 Year Commercial Limited Warranty
- Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

|   |  |
|---|--|
| Health & Wellbeing                      |  |
| Material Ingredient Transparency        | Health Product Declaration (HPD)   1000 ppm Disclosure                       |
| Indoor Air Quality                      | FloorScore®   Certified  |
| Climate Impact                          |  |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate)        | 9.4 Kg CO <sub>2</sub> /M <sup>2</sup>                                       |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)                                      |
| Global Product Assessment               | GSA   Approved   |
|   | CE Marking (EN 14041)   3rd Party Certified                                  |
|   | Country of Origin   Imported   |

WELL V2 Contribution Credit

|  |   |
|--|---|
| X01 Fundamental Material Precautions<br>Part 1: (C): Restrict Asbestos Precondition                    | Absence of Asbestos                     |
| X08 Hazardous Material Reduction<br>Part 1: Limit Hazardous Materials Optimization                     | Absence of Heavy Metals                 |
| X10 Volatile Compound Reduction<br>Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization   | Absence of Halogenated Flame Retardants |
| X10 Volatile Compound Reduction<br>Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization | Ortho-Phthalates                        |
| X11 Long Term Emissions Control<br>Part 2: Flooring Optimization                                       | FloorScore Certificate                  |

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

[Installation Guidelines](#)

[Maintenance Guidelines](#)

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**







**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

|  |   |   |  |   |   |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Pebble 96114<br>Weldrod 07332  | Tea Garden 96216<br>Weldrod 07332   | Zen 96515<br>Weldrod 01203  | Stroll 96535<br>Weldrod 02012  | Stepping Stone 96700<br>Weldrod 12155   | Pagoda 96710<br>Weldrod 05244   |